

TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 100300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 19 & 30; 24 & 25, T28-9

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 14 Page(s) 5787)

-----  
Set post cor. secs. 19, 30, 24 and 25, from which  
A Fir 30" dia., bears N.78°W., 31 lks. dist.  
A Fir 36" dia., bears S.65°W., 5 lks. dist.  
A Hemlock 24" dia., bears S.50°E., 5 lks. dist.  
A Yew 10" dia., bears N.32°W., 40 lks. dist.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; J. Fee, crew - Aug. 16, 1957 - C.S. File 49/12-1

-----  
Found - Orig. 8" now 10" dead Yewwood scribe marks visible N.32°W., 26.4 ft.  
Also rotted stumps for SW. and SE. BTs, check for bearing and distance.  
I find 40" Fir N.78°E., 20.4 ft. (Rec. N.78°W., 20.4 ft.) Shows old face near base, I do not open.

Set Brass cap at cor. mkd: County Surveyors Office

T 28 S  
R 9 W R 8 W  
S 24 | S 19  
S 25 | S 30  
1957

New BTs- 48" Hemlock N.85°W., 21.0 ft. scribed T28S R9W S24 DCS BT.  
12" Hemlock N.45½°E., 39.1 ft. scribed T28S R8W S19 DCS BT.  
7" Hemlock S.59°W., 9.8 ft. scribed T28S R9W S25 DCS BT.  
10" Hemlock S.79°E., 17.1 ft. scribed T28S R8W S30 DCS BT.

Cor. Fd. and Used in BLM Resurvey by William W. Glenn, Cadastral Surveyor, under Group #'s 350 and 420, surveyed April/June 1959 - (DCSO records Vol. 30 Page(s) 12852-53)

BLM remonumentation by Joseph S. Gawron, Cadastral Surveyor, under Group #350, surveyed April 1962 - (DCSO records - See C.S. File 49/12-20 (3<sup>rd</sup> & 4<sup>th</sup> pages - BLM pages 411-412)

-----  
The Sec. Cor., monumented with an iron pipe 1¼" dia., firmly set, protruding 14" above the ground, with brass cap mkd. in 1957 by DCSO  
from which the three remaining original bearing trees:  
(Cont. Next Page)

TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 100300

PRIMARY CORNER DESCRIPTION Sec. Cor. 19 & 30; 24 & 25, T28-9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Fir 48" dia., bears N.78°E., 31 lks., with healed blaze.  
A rotted Hemlock stump bears S.50°E., 5 lks. dist., with no marks remaining.  
A rotted Fir stump bears S.65°W., 5 lks. dist., with no marks remaining.  
and the county surveyors bearing trees:  
A Hemlock 12" dia., bears N.44°E., 60 lks. dist., mkd. T28S R8W S19 BT DCS.  
A Hemlock 12" dia., bears S.80¼°E., 25½ lks. dist. mkd. T28S R8W S30 BT DCS.  
A down Hemlock 8" dia., bears S.58 3/4°W., 15 lks. dist. mkd. T28S R9W S25 BT DCS.  
A down Hemlock 36" dia., bears N.85½°W., 31 lks. dist. mkd. T28S R9W S24 BT DCS.  
and two new bearing trees:  
A Hemlock 10" dia., bears S.12½°W., 30½ lks. dist. mkd. T28S R9W S25 BT.  
A Hemlock 13" dia., bears N.32°W., 138 lks. dist. mkd. T28S R9W S24 BT.  
Add the marks BLM 1962 to the County Surveyors brass cap.

Survey by Clyde Mulkins - For: Georgia Pacific - Nov. 30, 1994 - C.S. File 63/161-11  
-----  
Found - DCS0 2½" brass cap dated 1957 and stamped "BLM 1962". Sticks out of ground about 6".  
20" hemlock bears N.45°E., 39.3 ft. (Rec. N.45½°E., 39.1 ft.) Healed face, (1957 BT)  
25" Hemlock bears S.80°E., 17.2 ft. (Rec. S.79°E., 17.1 ft.) Healed face, (1957 BT)  
20" Hemlock bears S.12°W., 20.4 ft. (Rec. S.12½°W., 30.5 lks.) 1962 BLM  
New BT - 11" Hemlock bears N.39°W., 21 ft. scribed "S24 BT"

Coos County Surveyors Office - Michael Dado, Surveyor - Crew: Matthew Martin & Bill Hales - 12/22/2014 - C.S. File 65/87-29  
-----  
Found - 2½" brass cap on a 1¼" iron pipe, Douglas Co. Surveyor, 0.7' tall, in good condition but loose in the ground. We set a D.Fir post 3' north and paint the top in blue. 1957  
A 28" hemlock, N.47°E., 39.20' to found nail at left side center. We find a GP tag in place. We paint a band around the tree in blue. Good. 1957  
A 31" hemlock S.77°30'E., 17.36' to right side center. We find a healed blaze and 2 BLM tags in place. We paint the face and a band around the tree in blue. Good Condition 1957 Cont. next pg.

TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 100300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 19 & 30; 24 & 25, T28-9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A 22" hemlock, S.14°30'W., 20.39' to right side center. We find a healed blaze and 2 BLM tags in place. We paint the face and a bank around the tree in blue. Good condition. 1962

New B0- A 17" D.Fir stump, 1' tall, N.81°W., 39.21' to a spike and Coos County washer driven in at heart center. We paint the top of te stump in blue and attach a yellow Coos County tag.

Compass decl. 17°E.