

TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 100440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 18; S. 13, T28-9

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 14 Page 5787)

-----  
Set ¼ sec. post, from which  
A Yew 9" dia., bears N.20°W., 14 lks. dist.  
A Vine Maple 6" dia., N.70°E., 7 lks. dist.

Surveyor by Michael S. McDowell - For: Weyerhaeuser Co. - Dec. 22, 1975 - C.S. File 58/81

-----  
Set a 2" Iron pipe with brass cap, from which  
A scribed 6" Yew, bears N.44½°W., 15.4 ft.  
A scribed 24" Hemlock bears N.55°E., 27.4 ft.

BLM remonumentation by Aaron M. Graham, Cadastral Surveyor under Group #2012, surveyed April 2002/March 2003 - (DCSO rec. Vol. 54 Page(s) 21192)

-----  
The ¼ sec. cor. of sec. 13 & 18, reestablished by proportionate measurement by Michael S. McDowell, in 1975, recorded in the Coos County Surveyor's Office book 12 pg 204, & survey file 26a59. There is no remaining evidence of the original corner, therefore this position is accepted as the corner; monumented with an iron pipe, 2" dia., firmly set, projecting 24" above the ground, from which the remains of bearing trees mkd. by McDowell.

A fir stump, 36" dia., bears N.55°E., 27.6 ft., with a healed blaze.

A yew snag, 9" dia., bears N.43½°W., 15.4 ft., with scribe marks ¼ S13 BT visible in bark.

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd

T28S  
R9W R8W  
¼  
S 13|S 18  
2002

from which

A hemlock, 7" dia., bears N.39¾°E., 21.4 ft. mkd. ¼ S18 BT

A fir, 8" dia., bears S.77°W., 16.2 ft., mkd. ¼ S13 BT.

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center, unless otherwise described in the corner description

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Remove the 2" dia. iron pipe from the area.

continued next page

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

Coos County Surveyors Office - Michael Dado, Surveyor - Crew:  
Matthew Martin & Bill Hales - 12/16/2014 - C.S. File 65/87-26

- 
- Found - 3¼" brass cap, on a 2½" stainless steel pipe, 0.7' tall, in good condition and solid in the ground. We find a pitch post 3' North. Location Help: There is a 14" barely live Yew tree with a large chopped out face, N.5°W., 16'. 1976
- 24" Hemlock tall stump, 6' tall, N.56°E., 28.35' to top center. We find a healed blaze and both a BLM tag and a Weyco. tag in place. We paint the face in blue. POOR CONDITION. 1976
- 9" dead Yew tree, N.41°W., 15.24' to left side center. We find visible scribes, a Weyco nail in the face and both a BLM tag and a Weyco. tag in place. We paint the face in blue. Tree leans to the East, being held up by another Yew tree. POOR CONDITION. 1976
- 10" D.Fir, S.78°W., 16.37' to right side center. We find a healed blaze and a BLM tag in place. We paint the face and a band around the tree in blue. GOOD CONDITION. 2002
- 11" Hemlock, N.41°E., 21.21' to right side center. We find visible scribes in an open blaze and a BLM tag in place. We paint the face and a band around the tree in blue. GOOD CONDITION 2002
- New BT- An 8" D.Fir, N.85°E., 19.80' to a nail at left side center. We blaze and scribe "¼ S18 BT". We paint the blaze, scribes and a band around the tree in blue and attach a yellow Coos County tag.
- A 19" Hemlock, N.41°W., 16.79' to a nail at right side center. We bark scribe "¼ S13 BT". We paint the scribes and a band around the tree in blue and attach a yellow Coos County tag.
- Note - Warren Knight Staff Compass - declination 17°E.