

TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 100540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 7; & 12, T28-9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 14 Page(s) 5786)

Set ¼ sec. post, from which
A Yew 9" dia., bears S.85°E., 25 lks. dist.
A Yew 12" dia., bears S.70°W., 60 lks. dist.

Douglas County Surveyors Office - J. Powell and crew - C.S. File 54/113-6 - April 22, 1970

Corner searched for, not found.
This falls in cut unit about 250 ft. West of Kenner Creek Road. Found (no record):
53" D.Fir snag blazed and scribed ¼S S.88°W., 59.0 ft.
Also squared stake at approx. cor.
Also found Yew stump out of ground, possible BT. No scribing.

Harvey Christensen - Dec. 30, 1998, Recorded 11/13/2001 - C.S. File 65/40-4

Found - 60" Fir snag ±30' high, with partly open blaze with rotten face (this BT established by C.S. Lehmanowskey in June 1958 C.S. Bk 9 Page 167) {Coos County surveyor and record #?}
Set - 5/8" rebar, 36" long at rec. bearing & dist. (N.88°30'E., 52.0' Lehmanowsky) from fd. 60" fir snag BT. 5/8" rebar has yellow plastic cap marked "LS 2603", falls on NE slope.
14" Fir N.87¼°E., 5.4' to ctr., blazed & scribed "¼ S7 BT"
11" Fir S.12°E., 11.3' to ctr. blazed & scribed "¼ S7 BT"
15" Fir S.50°W., 29.9' to ctr. blazed & scribed "¼ S12 BT"
9" Fir N.28°W., 29.8' to ctr. blazed & scribed "¼ S12 BT"
Note - Falls ±25' South of drainage flowing East & falls West ±250' from Knepper Creek Road.