

PRIMARY CORNER DESCRIPTION Sec. Cor. for 6 & 7; 1 & 12, T28-9

Alias	Description
Alias	Description
Alias	Description
Alias	Description

BLM remonumentation by Aaron M. Graham, Cadastral Surveyor under Group #2012, surveyed April 2002/March 2003 - (DCSO rec. Vol. 54 Page(s) 21194-5)

The cor. of secs. 1, 6, 7, & 12, on the E. bdy. of the Tp., perpetuated by Forrest J. LaFlamme, in 1962, recorded in the Coos County Surveyor's Office, Book 10, pg 168, subsequently perpetuated by the Douglas County Surveyor's Office, in 1970, further perpetuated by Christensen, in 1999, recorded in the Coos County Surveyor's Office book 16, pg 103; monumented with an iron post, 1" dia., firmly set, projecting 10" above the ground, with brass cap (properly) mkd.

from which the remains of the original bearing trees

A root hole, bears N.40°E., 9.2 ft., with a fir log alongside, 40" dia., no marks visible.

A fir stump, 33" dia., bears S.75°E., 16.5 ft. no marks visible.

A fir stump, 61" dia. bears S.47¾°W., 32.5 ft. with scribe marks S12 BT visible on open blaze (Rec S.45°W. 30.4 ft)

A fir stump, 25" dia., bears N.40°W., 29.0 ft. no marks visible.

and the remains of bearing trees mkd. LaFlamme in 1962

A fir stump, 36" dia., bears S.35¾° E., 38.5 ft., with scribe marks S7 BT 47 visible on open blaze.

and the remains of bearing trees mkd. by the Douglas County Surveyor's Office in 1970

A fir stump, 53" dia., bears S.80¾° E., 27.8 ft., with scribe marks T28S R8W S7 C BT visible on partially healed blaze.

A hemlock, 28" dia., bears S.81½°W., 85.5 ft., with a healed blaze.

and bearing trees mkd. by Christensen in 1999

A fir, 10" dia., bears N.59°E., 38.2 ft., with scribe marks T28S R8W S6 BT visible on partially healed blaze.

A fir, 9" dia., bears S.50½°E., 14.6 ft., with scribe marks T28S R8W S7 BT visible on partially healed blaze.

A fir, 14" dia., bears N.53½°W., 39.9 ft., with scribe marks T28S R9W S1 BT visible on partially healed blaze.