

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William P. Heyden, Deputy Surveyor, under contract #656, dated May 21, 1896 - (DCSO records Vol. 13 Page(s) 5283)

Set Yew post 3 ft. long, 4" sq., 24" in the ground, for standard ¼ sec. cor. mkd. S C ¼ S on N. face, from which
A Yew 10" dia., bears N.40°E., 25 lks. dist. mkd. S C ¼ S BT.
A Fir 36" dia., bears N.50°W., 17 lks. dist. mkd. S C ¼ S BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - April 23, 1970 - C.S. File 54/113-7

Found - 10" now 12" Yew, N.10°E., (Rec. N.40°E.) 16.5 ft., scribe visible, scribe partly done with knife.
36" now 38" D.Fir N.50°W., 11.2 ft., shows faint bark scribe "SC" done with scribe, definitely old enough. Other bark scribe with knife, "¼S BT".
Set Brass cap at cor. mkd: County Surveyors Office
T 27 S R8W ¼ S 31
T 28 S
1970

Reblazed and rescribed:
38" D.Fir N.50°W., 11.2 ft. mkd. ¼ S31 CS BT.
New BT - 16" Hemlock N.55°E., 23.7 ft. mkd. ¼ S31 CS BT.

BLM remonumentation by Aaron M. Graham, Cadastral Surveyor under Group #2012, surveyed April 2002/March 2003 - (DCSO rec. Vol. 54 Page(s) 21182-3)

This point, the ¼ sec. cor. of sec. 31 only, on the S. bdy of T27S R8W perpetuated by the Douglas County Surveyor's Office in 1970, C.S. file 54/113, bears N.89°19'14"E., 2198.64 ft. (this control line was retraced and search was made for the intermediate line tree, which was not recovered), monumented with an iron post, 1½" dia., firmly set, projecting 2" above the ground, with brass cap (properly) mkd., from which the remains of the original bearing trees
A yew stump, 14" dia., bears N.12¾°E., 15.5ft., with no scribe marks visible on burned blaze. (Record, N.40°E., 16.5 ft.)
A fir stump, 42" dia., bears N.50°W., 11.2 ft., with fragmentary scribe marks visible on open blaze.
and new bearing trees
A fir, 8" dia., bears N.18°E., 11.5 ft., mkd. X at breast height and BT at base. continued next page

TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 133700

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. Sec. 31 only, T27-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir, 8" dia., bears N.35 $\frac{3}{4}$ °W., 23.8 ft., mkd. $\frac{1}{4}$ S31 BT.
Each new bearing tree has a 2 $\frac{1}{2}$ "x $\frac{1}{4}$ " magnetic nail (Mag Nail)
driven at the base right side-center, unless otherwise
described in the corner description