

TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 140200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 30 and 31

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 14 Pg 5813)

Set ¼ sec. post, from which
A Fir 12" dia., bears N.4°E., 82 lks. dist.
A Fir 10" dia., bears S.36°W., 13 lks. dist.

BLM resurvey by John Jelley, Cadastral Surveyor, Group #552, surveyed July. 1964 - (DCSO records Vol. 32 Page(s) 13572-73)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:
T 28 S R 8 W
¼ $\frac{S\ 30}{S\ 31}$
1964

from which
A Fir 10" dia., bears N.61½°W., 28½ lks., mkd. ¼ S30 BT.
A Fir 9" dia., bears S.8½°W., 58½ lks. mkd. ¼ S31 BT.
The corner falls on a spur, slopes SE.
From this point, an iron pipe 1/2" dia., 4" above ground, firmly set, bears N.82°E., 0.32 chs.

Bruce Shaner - for Superior Lumber Co. June 1993; M112-78 C.S. 63/153 -16

Found 3¼" Brass Cap on a 2" IP properly mkd from which:
22" D.Fir (rec. 10"), face overgrown, bears N.61½°W., 18.8'
12" D.Fir (rec. 9"), face overgrown, bears S.8¼°W., 38.6'
New Accessories -
10" D.Fir, bears S26°W., 6.4 ft. Scribed "¼ S31 BT"
16" D.Fir, bears N.12½°E., 63.1 ft. Scribed "¼ S30 BT"
Corner is N.60°W. ± 500 ft. from where logging road crosses live stream.

BLM resurvey by George M. Winter, Cadastral Surveyor, group No. 2500 Admin File No. 1303, surveyed March/May 2013 - (DCSO records BLM Plat T28-8W, 2014-1 & Vol. 58 Page 23053)

The ¼ sec. cor. of secs. 30 & 31, perpetuated by Shaner, in 1993, monumented with an iron post, 2½" dia., firmly set, projecting 4" above ground, with brass cap (properly mkd.) from which the remaining BT mkd. by Jelley in 1964
A fir, 15" dia., bears S. 8½°W., 38.6 ft., with a healed blaze.
and the remains of bearing trees mkd. by Shaner (cont.)

TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 140200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 30 and 31

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir stump, 20" dia., bears N.7¼°E., 63.2 ft., with a healed blaze.
A fir, 11" dia., bears S.21¾°W., 6.4 ft., with a healed blaze.
and a new bearing tree
A fir, 10" dia., bears N.50½°W., 12.6 ft., mkd. ¼ S30 BT.
NAD 1983 (2011)
Latitude 43°05'53.00" N Longitude 123°41'30.72" W

BLM survey by Scott Toldness - PLS 90216 - Glahe & Associates
Professional Land Surveyors - 2024

Found - A 3¼" BLM brass cap on a 2½" iron post, 0.3' above ground with an aluminum post east 1.0'.
A Fir 36" diam bears S.33°E. 68.4' dist with healed blaze and tag by Herak and Mayer 4/58.
A Fir 12" diam bears S.21½°W. 6.4' with healed blaze and tag by JMT 7/64
A Fir 16" diam bears S.9¼°W. 38.6' with healed blaze and tag by Shaner 7/23/93.
A Fir 11" diam bears N.52°W. 12.6' with healed blaze and tag by MM 4/13.

New - Added post E. 5' and W. 5' with boundary signs.
Added paint, blazes, and tags to Bts.
Added nails at side center of the two S.W. Bts.