

TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 140500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 7 and 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W. S. Chapman, Deputy Surveyor, under Contract #234, dated June 24, 1875 - (DCSO records Vol. 14 Page(s) 5827)

Set post 4 ft. long, 4" dia., 1 ft. in the ground, for ¼ sec. post, from which

A Fir 40" dia., bears S.70°W., 17 lks. dist.

A Yew 8" dia., bears S.25°W., 65 lks. dist.

This cor. is on precipitous slope, facing South.

BLM Resurvey by Lynn Roseberry; Daniel Berry; Gordon Popken and Albert Garrison, Cadastral Surveyors, under Group #'s 691 and 764, Surveyed June, 1969/April 1973 - (DCSO records Vol. 36 Page(s) 15093)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Seat a brass tablet, 3¼" dia., 3½" stem, in a drill hole, in solid rock, with top mkd:

T 28 S R 8 W

1/4 $\frac{S 7}{S 18}$

1972

from which

A Fir 12" dia., bears N.16¼°E., 140½ lks. dist. mkd. ¼ S7 BT.

A Fir 10" dia., bears S.82¼°W., 147 lks. dist. mkd. ¼ S18 BT.