TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 200140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 31 and 32

Alias Description
Alias Description
Alias Description
Alias Description

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 14 Page(s) 5811-12)

Set ¼ sec. post, from which
A Cedar 20" dia., bears S.80°E., 21 lks. dist.
A Fir 18" dia., bears N.66°W., 29 lks. dist.

BLM resurvey by John Jelley, Cadastral Surveyor, Group #552, surveyed July. 1964 - (DCSO records Vol. 32 Page(s) 13571)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd: T 28 S R 8 W

¼
S 31|S 32
1964

from which
A Fir 16" dia., bears N.77°E., 161 lks. dist. mkd. ¼ S32 BT.
A Cedar 7" dia., bears S.81°W., 78½ lks. dist., mkd. ¼ S31 BT.
From this point, an iron pipe, 1½" dia., 5" above ground, firmly set, and in a barbed wire fence which bears N. and S., bears S.26°E., 0.125 chs. dist.

Fd. Ok by Ed Farr, 3/2006 - 2006-0039A&B