

TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 200240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 29 and 30

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W. S. Chapman, Deputy Surveyor, under Contract #234, dated June 24, 1875 - (DCSO records Vol. 14 Page(s) 5822)

Set post 4 ft. long, 4" dia. and 1 ft. in ground, for ¼ sec. cor., from which
A Cedar 20" dia., bears S.50°E., 60 lks. dist.
A Fir 20" dia., bears N.45°W., 120 lks. dist.

Survey by Ronald E. Stuntzner - For: Dr. & Mrs. Keizer - April 1977 - M 64-3

Set 5/8" Iron rod with steel post, from which
14" Madrone N.81°W., 28.8 ft., tagged and scribed.
16" Fir N.79°E., 18.5 ft. tagged and scribed.

Bruce Shaner - For: Superior Lumber Co. June 1993; M112-78 C.S. File 63/153-20

Found - 5/8" x 34" Iron Rod w/plastic cap, from which:
18" D.Fir stump (rec. 16") scribes "BT" visible bears N.84°E., 18.5 ft. (rec. N.79°E.)
16" Madrone (rec. 14") scribes "¼" visible bears N.75°W., 28.8 ft. (rec. N.81°W.)

Set 2½" Brass Cap mounted on a 1" x 30" iron pipe in place of the 5/8" iron rod & then placed iron rod alongside Brass Cap. Brass Cap marked: SHANER ENGR

1/4 S
S 30 | S 29
T28S R8W WM
RLS 430 1993

New Accessories -

6" D.Fir, bears N.80°E., 4.6 ft. scribed "¼ S29 BT"
14" Cedar, Bears N.62°E., 13.8 ft. scribed "¼ S29 BT"
8" W.Fir bears S.60°W., 8.0 ft. scribed "¼ S30 BT"
Corner is approx 1000 ft. west of logging road.

Fd. OK by McLind, June 1998 - M 128-76