

TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 200340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 19 and 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W. S. Chapman, Deputy Surveyor, under Contract #234, dated June 24, 1875 - (DCSO records Vol. 14 Page(s) 5824)

Set post 4 ft. long, 4" dia., 1 ft. in the ground for ¼ sec. cor., from which
A Fir 42" dia., bears West, 8 lks. dist.
A Chinquapin 15" dia., bears N.15°E., 35 lks. dist.

Douglas Co. Surveyors Office - John M. Powell, and crew - April 20, 1970 - C.S. File 54/113-3

Looked for, not found.
One large D.Fir found, old location tag near approx. cor. No trace of BT logged and burned.

BLM Resurvey by Lynn Roseberry; Daniel Berry; Gordon Popken and Albert Garrison, Cadastral Surveyors, under Group #'s 691 and 764, Surveyed June, 1969/April 1973 - (DCSO records Vol. 36 Page(s) 15086-87)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:
T 28 S R 8 W
1/4
S 19 | S 20
1972

from which
A Cedar 35" dia., bears N.61°E., 56 lks. dist. mkd. ¼ S20 BT.
A Hemlock 6" dia., bears S.67°W., 53 lks. dist. mkd. ¼ S19 BT.

Fd. OK, July 16, 1985 by R. Geisler - C.S. File 63/22-2