

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7, 8, 17 and 18

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

GLO survey by W. S. Chapman, Deputy Surveyor, under Contract #234, dated June 24, 1875 - (DCSO records Vol. 14 Page(s) 5824)

 Set post 4 ft. long, 5" dia., 1 ft. in the ground, for cor. of secs. 7, 8, 17 and 18, from which
 A Fir 44" dia., bears S.25°W., 102 lks. dist.
 A Fir 32" dia., bears S.15°E., 58 lks. dist.
 A Fir 24" dia., bears N.70°W., 154 lks. dist.
 No other tree within reach.

BLM Resurvey by Lynn Roseberry; Daniel Berry; Gordon Popken and Albert Garrison, Cadastral Surveyors, under Group #'s 691 and 764, Surveyed June, 1969/April 1973 - (DCSO records Vol. 36 Page(s) 15091)

 Point for the sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
 Set an iron post, 28" long, 2 1/2" dia., 26" in the ground, with brass cap mkd:

T	28	S	R	8	W
	S	7	S	8	
	S	18	S	17	
				1972	

from which
 A Fir 15" dia., bears N.37°E., 54 lks. dist. mkd. T28S R8W S8 BT.
 A Fir 8" dia., bears S.62°E., 42 lks. dist. mkd. T28S R8W S17 BT.
 A Fir 18" dia., bears S.17°W., 39 lks. dist. mkd. T28S R8W S18 BT.
 A Fir 18" dia., bears N.40°W., 15 lks. dist. mkd. T28S R8W S7 BT.

Douglas Co. Surveyors Office - Randall Smith and Stephen Flause, crew - Aug. 9, 1984 - C.S. File 62/21-37

 Found - 1972 BLM disk on I.P., firmly set, protruding 4" above ground and properly marked.
 16" DBH D.Fir bears N.37°E., 35.1 ft. (Rec. 1972, a Fir 15" bears N.37°E., 54 lks. slope dist. to cap) has healed single blaze, no scribing visible.
 8" Fir now a 9" DBH D.Fir bears S.62°E., 27.7 ft. Tree has healed single blaze, no scribing visible.
 18" Fir now a 20" DBH D.Fir bears S.17°W., 25.7 ft. Tree has healed single blaze, no scribing visible.
 (Cont. Next Page)

TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 200500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7, 8, 17 and 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

An 18" Fir now a 20" DBH D.Fir bears N.40°W., 9.9 ft. Tree has healed single blaze, no scribing visible.
Trees are all properly tagged except as noted in new accessories.
New Accessory:
Tag on NE. Bt altered; distance changed to 35.1 ft. to indicate horizontal distance between cap and center of BT root crown. Added initials DCSO to tag.
Monument lies down steep South slope approx. 250 ft. horz. distance from BLM Road 28-8-20.

BLM resurvey by A. Bert Skeesick Cadastral Surveyor & Robert H. Browning, Surveying Tech. under Group #2100, surveyed Sept. 2004 - (DCSO rec. Vol. 55 Page 21500) & 2008 BLM plat

The corner descriptions are as reported by Roseberry. et al, in 1969-73.
NAD 1983 (CORS)
Latitude 43°07'37.59"N
Longitude 123°40'56.14"W