

PRIMARY CORNER DESCRIPTION Sec. Cor. for 5, 6, 7 and 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 Survey by George S. Pershin, under Contract #238, Dated, July 13, 1875 - (DCSO records Vol. 14 Page(s) 5828)

Set Hemlock post for cor. to secs. 5, 6, 7 and 8, from which
 A Hemlock 6" dia., bears N.35°E., 23 lks. dist.
 A Hemlock 36" dia., bears N.24°W., 60 lks. dist.
 A Hemlock 14" dia., bears S.10°W., 59 lks. dist.
 A Yew 10" dia., bears S.50°E., 22 lks. dist.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; J. Fee, crew - July/Aug. 1957 - C.S. File 49/5-3

Found - Orig. 36" Hemlock, good scribing, open face.
 N.24°W., 39.6 ft.
 Base of small rotted Hemlock stump N.35°E., 15.2 ft.
 15" Ewewood S.42°E., 14.5 ft., shows old weathered
 face, no scribing. Found checks for orig. SE. BT
 dist. only.
 Orig. SW. BT not found.

Set Brass cap at cor. mkd: County Surveyors Office
 T 28 S R 8 W
 S 6 | S 5
 S 7 | S 8
 1957

New BTs- 18" Hemlock S.13°W., 37.6 ft. scribed S7 T28S R8W CS
 BT.
 15" Ewewood S.42°E., 14.5 ft. scribed S7 T28S R8W CS
 BT.
 6" Hemlock N.2°E., 52.2 ft. scribed S5 CS BT.

BLM Remonumentation by Wayne L. Rogers, Cadastral Surveyor, under Group #350, surveyed Aug. 1973 - (DCSO records Vol. 38 Page(s) 15563)

The Sec. Cor. perpetuated and recorded by DCSO in 1957, monumented with an iron post 1½" dia., firmly set, projecting 12" above ground with brass cap mkd. in 1957 from which the remains of the original bearing trees
 A root hole bears S.50°E., 22 lks. dist. with a down Yew alongside, 14" dia., with scribe marks T28S R8 visible on open blaze.
 A Hemlock snag 14" dia., bears N.24°W., 60 lks dist., with scribe marks T28S R8W S6 BT visible on open blaze.
 and new bearing trees
 A Yew 22" dia., bears N.89°E., 139 lks. dist. mkd. T28S R8W S5 BT.

(Cont. Next Page)

TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 200600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 5, 6, 7 and 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Hemlock 12" dia., bears N.31½°W., 152 lks. dist. mkd.
T28S R8W S6 BT.

BLM resurvey by James E. Jelley, Cadastral Surveyor - under
Group #863, surveyed May/July 1975 - (DCS0 records Vol. 38
Page(s) 15592-93)

The Sec. Cor. perpetuated and recorded by Byron in 1957,
monumented with an iron post 1½" dia., firmly set, projecting
10" above ground with brass cap mkd. in 1957

from which the remains of the original bearing trees;
A root hole bears S.42°E., 16 lks. dist., with a down Yew
alongside 12" dia., no marks visible on decayed blaze.
Rescribed by Byron with scribe marks T28S R8W S8 CS
visible on open blaze. (Rec. S.50°E., 22 lks.)

A Hemlock snag 48" dia., bears N.24°W., 60 lks. dist. with
scribe marks T28S R8W S6 BT visible on open blaze.
and the remains of bearing trees mkd. by Byron

A root hole bears N.2°E., 79 lks. dist., with a down
Hemlock alongside 6" dia., with scribe marks S5 CS
visible on open blaze.

A root hole bears S.42°E., 16 lks. dist. with a down
Hemlock alongside 12" dia., with scribe marks T28S R8W
S CS visible on open blaze.

A root hole bears S.13°W., 53 lks. dist., with a down
Hemlock alongside 17" dia., with scribe marks T28S R8W
S7 CS BT visible on open blaze.

and bearing trees not of record
A Yew 20" dia., bears N.89°E., 137 lks. dist. with scribe
marks T28S R8W S5 BT visible on open blaze.

A Hemlock 15" dia., bears N.31½°W., 148 lks. dist., with
scribe marks T28S R8W S6 BT visible on open blaze.

and new bearing trees
A Yew 10" dia., bears S.9 3/4°E., 245 lks. dist. mkd. T28S
R8W S8 BT.

A Hemlock 29" dia., bears S.55 3/4°W., 464 lks. dist. mkd.
T28S R8W S7 BT.

Douglas Co. Surveyors Office - Crew: Stephen J Flause & Jeff
Lorsung - 11/14/2018 (filed 2/16/2021) - C.S. File 67/49-1

Found - A 1" Id. iron pipe by Byron in 1957, firmly set,
projecting 12" above the ground with a 2½" brass
cap (properly) marked

Original BTs by Pershin in 1875:
A 39"x17' tall rotted Hemlock snag bears N.24°W.,
39.6 ft with scribe marks "T28S R8 S6 BT" visible

continued next page

TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 200600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 5, 6, 7 and 8

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

A root hole bears (S.42°E., 10.6 ft. per 1975 USBLM Record) with an uprooted 15" Yew alongside and buried under uprooted old growth fir. Unable to measure to actual root hole because of the uprooted fir

There is no remaining evidence of BTs scribed by Byron in 1957 or BTs found or scribed by Jelley in 1975.

New - A 14" D.Fir bears N.44°E., 11.6 ft. scribed "T28S R8W S5" "CS BT".

A 17" hemlock bears S.51½°E., 10.7 ft. scribed "X", "BT" (tree has furrowed face, standard blaze not possible).

A 21" D.Fir bears S.82°W. 26.2 ft scribed "T28S R8W S7 CS" "BT".

Note - All BTs have BT tags attached. All new BTs have double blazed faces with bearings measured to the center of the tree at the root crown and distances measured to a 2½" PK nail in the side and center of the root crown

Corner falls on a gentle NNW slope in older fir and hemlock reprod. timber.

Declination 15°E.