

TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 200640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 5 and 6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by George S. Pershin, under Contract #238, Dated, July 13, 1875 - (DCSO records Vol. 14 Page(s) 5830)

Set Yew post for ¼ sec. cor., from which
A Cedar 10" dia., bears East, 31 lks. dist.
A Yew 6" dia., bears S.50°W., 16 lks. dist.

BLM resurvey by James E. Jelley, Cadastral Surveyor - under Group #863, surveyed May/July 1975 - (DCSO records Vol. 38 Page(s) 15593)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

¼
S 6 S 5
T 28 S R 8 W
1975

from which

A Cedar 25" dia., bears S.41°E., 50½ lks. dist. mkd. ¼ S5
BT.

A Cedar 32" dia., bears S.81°W., 27½ lks. dist. mkd. ¼ S6
BT.