

TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 200700

PRIMARY CORNER DESCRIPTION C C for Secs. 5 & 6 only (North)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 14 Page(s) 5785)

Set post, cor. secs. 5 and 6, from which
A Fir 30" dia., bears S.48°W., 53 lks.
A Fir 36" dia., bears S.50°E., 46 lks.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; J. Fee, crew - July/Aug. 1957 - C.S. File 49/5-4

Found - Orig. 30" now 36" Fir, S.48°W., 35.0 ft. Good bark scribing. BT in good condition.
Orig. 36" now 35" Fir, S.50°E. Record distance 46 lks., I find it to be 26 lks. Good bark scribing, tree alive and in good condition. BTs face to corner as located.

Also found 8" Ewewood N.64½°W., 10.0 ft. scribed S5 on East side and S6 on West side. (Not old scibing, may be about 15 years old.)

Set Brass cap at cor. mkd: County Surveyors Office
T27½S R8W

S6 | S5
T28S R8W
1957

New BTs- 12" Ewewood bears S.31°W., 14.4 ft. scribed T28S R8W S6 CS BT.
7" Hemlock bears S.83°E., 20.0 ft. scribed S5 CS BT.
6" Ewewood bears N.68°W., 32.8 ft. scribed T27S R8W S32 CS BT.

BLM Resurvey by C. Albert White; John M. Jelley; James E. Jelley, Cadastral Surveyors, Under group #466, Surveyed Sept/Oct. 1961 - (DCSO records Vol. 30 Page(s) 12864-65)

The standard cor. of secs. 5 and 6, remonumented by the DCSO with an iron post, 1" dia., protruding 12" above ground with brass cap mkd. as noted in 1957, from which the original bearing trees:

A Fir 36" dia., bears S.50°E., 26 lks. dist. bark scribed T28S R8 and other illegible scribe marks. (Rec. 46 lks. dist.)

A Fir 62" dia., bears S.46°W., 55 lks. dist. bark scribed T28S R8W S6 (Rec. bears S.48°W., 53 lks.)

and trees mkd. by the County:
(Cont. Next Page)

TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 200700

PRIMARY CORNER DESCRIPTION C C for Secs. 5 & 6 only, North

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A Hemlock 8" dia., bears S.84°E., 30 lks. dist., mkd. S5 CS BT.

A Yew 10" dia., bears S.30°W., 22 lks. dist. mkd. T28S R8W S6 CS BT.

A Yew 6" dia., bears N.71°W., 49 lks. dist. mkd. T27S R8W S32 CS BT.

and a tree mkd. by Boyer, RPE 1581:

A Yew 6" dia., squared at breast height, bears N.68°W., 15 lks. dist., mkd. S5 on E. face and S6 on W. face.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

	S 6	S 5
T 28	S	R 8 W
	S C	
	1961	

from which a new bearing tree:

A Fir 58" dia., bears S.29°E., 28 lks. dist. mkd. T28S R8W S5 SC BT.

Add the marks SC BT in the bark on original SW. tree.

Deposit DCS0 iron post alongside the corner post.

BLM resurvey by James E. Jelley, Cadastral Surveyor - under Group #863, surveyed May/July 1975 - (DCS0 records Vol. 38 Page(s) 15594)

(corner found and used in this survey. Jelley added "Add marks 1975 to brass cap")

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2500 admin file No. 1201, Surveyed April/May 2012 - (DCS0 records Survey plat 2012-1 A&B & Vol. 58 Page(s) 22763-4)

The standard cor. of secs. 5 and 6, on the N. bdy. of T. 28 S., R. 8 W., monumented with an iron post, 2½" dia., firmly set, projecting 3" above ground, (alongside of which is an iron post, 1¼" dia., firmly set, bent N., projecting 8" above ground, with a brass cap mkd. COUNTY SURVEYORS OFFICE T27S R8W S 32 6 5 T28S R8W 1957) with brass cap (properly) mkd. from which the remains of the original BTs mkd. by Hathorn

A sawed fir stump, 32" dia., bears S.50°E., 17.2 ft. with a healed blaze and metal cover

A sawed fir stump, 60" dia., bears S.46°W., 36.3 ft., with no marks visible.

and the remains of a BT Byron in 1957

A hemlock snag 10" dia., bears S.84°E., 19.8 ft., with no marks visible and a metal cover. continued next page

TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 200700

PRIMARY CORNER DESCRIPTION C C for Secs. 5 & 6 only (North)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and the remains of a bearing tree mkd. by White, et al.
A sawed, decayed fir stump, 58" dia. bears S.29°E., 18.5 ft. with scribe marks T28S R visible on a partially healed blaze.

and the remains of a reference tree by person(s) unknown
A sawed, decayed hemlock stump, 43" dia, bears N.28°E., 23.3 ft. with axe marks visible, a nail stamped "W" driven in base facing the cor. and a metal cover.

and new bearing trees mkd.
A fir, 7" dia., bears S.43°E., 23.3 ft., 13.2 ft., mkd. T28S R8W S5 BT.
A fir, 9" dia., bears S.36¾°W., 10.5 ft. mkd. T28S R8W S6 BT.