

TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 300100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 32 & 33; 4 & 5, T29-8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 14 Page(s) 5794)

Set post cor. secs. 32, 33, 4 and 5, from which
A Fir 24" dia., bears S.40°W., 25 lks. dist.
A Fir 15" dia., bears N.15°W., 43 lks. dist.
A Laurel 10" dia., bears N.50°E., 31 lks. dist.
A Laurel 10" dia., bears S.10°E., 25 lks. dist.

Douglas Co. Surveyors Office - James Byron, Deputy - S. Bilow, crew - Sept. 9, 1957 - C.S. File 49/12-10

Found - Orig. 24" now 32" Fir, S.40°W., 16.5 ft. I open and find good scribing "S 5".
Find 15" now 24" Fir N.15°W., 28.4 ft., shows old face. I do not open.

Checks brg. & dist., using old faces for distances. Set Brass cap at cor. mkd: County Surveyors Office, 1957

32	33	T28S
5	4	T29S

New BTs- I rescribe, bark, the orig. N.15°W. BT, new distance 29.4 ft., "T28S R8W S32 CS BT"

Bark scribe 48" R.Fir, N.7°E., 14.0 ft. "T28S R8W S33 CS BT"

Blaze & scribe 9" Cedar S.9°E., 17.6 ft. "T29S R8W S4 CS BT"

The original SW. bearing tree is in good condition.

BLM resurvey by James E. Jelley, Cadastral Surveyor - under Group #863, surveyed May/July 1975 - (DCSO records Vol. 38 Page(s) 15576)

The Sec. Cor., perpetuated and recorded by Byron in 1957, monumented with an ironpost, 1½" dia., firmly set, projecting 10" above ground, with brass cap mkd. in 1957

from which the remains of the original bearing trees:

A Fir snag 30" dia., bears S.42°W., 27 lks. dist., with fragmentary scribe marks visible on open blaze. (Rec. S.40°W., 25 lks., to face.

and bearing trees mkd. by Byron:

A Fir 50" dia., bears N.8°E., 21 lks. dist., with scribe marks T29S R8W S4 CS BT visible on open blaze.

A Cedar 11" dia., bears S.10°E., 26½ lks. dist., with scribe marks T29S R8W S4 CS BT visible on open blaze.

and new bearing trees

(Cont. Next Page)

TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 300100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 32 & 33; 4 & 5, T29-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A W.Fir 5" dia., bears S.11¼°W., 55 lks. dist.mkd. T29S
R8W S5 BT.

A Fir 12" dia., bears N.74 3/4°W., 248 lks. dist. mkd.
T28S R8W S32 BT.

FD. BC & 3 BTs, Set 6' steel post 2' south, by D. Edwards,
7/2011 - C.S. File 65/74-8