TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 300140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 32 and 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 14 Page(s) 5811)

Set ¼ sec. post, from which
A Cedar 20" dia., bears S.79°W., 90 lks. dist.
A Fir 12" dia., bears N.55°E., 86 lks. dist.

BLM resurvey by James E. Jelley, Cadastral Surveyor - under Group #863, surveyed May/July 1975 - (DCSO records Vol. 38 Page(s) 15577)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd: ¼
S 32 S 33
T 28 S R 8 W
1975
from which bearing trees not of record:
A W.Fir 10" dia., bears N.49°E., 62 lks. dist. with scribe marks ¼ S33 T28S R8W BT 760 visible on open blaze.
A W.Fir 12" dia., bears S.65 3/4°W., 65 lks. dist., with scribe marks ¼ S32 T28S R8W BT visible on open blaze.

Herbert Northcraft - For: G.W. Tipton - 1969 survey filed Dec. 1989 - M 109-16)

Set - 3/4" I.R.
10" Fir N.30°E., 40.2', mkd: ¼ S33 T28S R8W BT 750
12" W.Fir S.81°W., 51.3', mkd: ¼ S32 T28s R8W BT 750
NOTE: The map wasn't made or filed in which shows that we (Northcraft) set the E¼ of with trees as noted. A dependent resurvey in 1975 of the E. line of Sec. 32 didn't find a 3/4" I.R. that we set, but Fd. The witness trees that we set & used them.