

TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 300300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 20, 21, 28 and 29

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W. S. Chapman, Deputy Surveyor, under Contract #234, dated June 24, 1875 - (DCSO records Vol. 14 Page(s) 5817)

Set post 4 ft. long, 5" dia. and 1 ft. in ground, for cor. of secs. 20, 21, 28 and 29, from which
A Fir 36" dia., bears N.10°E., 27 lks. dist.
A Chinquapin 4" dia., bears S.35°W., 40 lks. dist.
A Maple 4" dia., bears N.30°W., 18 lks. dist.
A Fir 20" dia., bears S.30°E., 38 lks. dist.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; J. Fee, crew - July/Aug. 1957 - C.S. File 49/5-18

Found - 20" now 40" R.Fir S.30°E., 25.1 ft. I open old face and find good scribing "BT".
50" R.Fir N.10°E., 17.8 ft. which is record bearing and distance for original NE. BT. I open and find old face but no scribe markings found.
Set Brass cap at cor. mkd: County Surveyors Office
T 28 S R 8 W
S 20 | S 21
S 29 | S 28
1957

New BTs- 10" R.Fir bears S.46½°E., 41.6 ft. scribed S28 T28S R8W CS BT.
50" R.Fir bears N.10°E., 17.8 ft. rescribed old face "S21 T28S R8W CS BT"
8" Maple bears N.16°W., 13.6 ft. scribed S20 CS BT.
6" Chinquapin bears S.34½°W., 26.0 ft. scribed S29 CS BT.

Cor. Fd. and used in BLM Resurvey by Lynn Roseberry; Daniel Berry; Gordon Popken and Albert Garrison, Cadastral Surveyors, under Group #'s 691 and 764, Surveyed June, 1969/April 1973 - (DCSO records Vol. 36 Page(s) 15084)

Cor. Fd. and used in BLM resurvey by James E. Jelley, Cadastral Surveyor - under Group #863, surveyed May/July 1975 - (DCSO records Vol. 38 Page(s) 15580)

Found OK by T. Rambo, Sept. 2002 - M141-11

continued next page

TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 300300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 20, 21, 28 and 29

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Mark Smalley, Roseburg Forest Products - Party Chief: William Olson - May 2009 - C.S. File 65/66-26

Found - 1957 DCS0 brass cap
46" Fir S.30°E., 25.6' (Recorded 25.1') Healed face
1875
13" Maple N.16°W., 13.4' (Recorded 13.6') Healed
face 1957
14" Chinquapin S.34½°W., 25.5' (Recorded 26.0')
Healed face 1957
10" R.Fir S.46½°E., 41.6' 1957 GONE
50" R.Fir N.10°E., 17.8' 1875 GONE
New - 40" D.Fir N.8°E., 49.6' measured to a nail in the
side-center of stump Scribed "S21BT" with LS 2354
brass washer.
Note - Compass decl. 18°E.

Fd. ok - R. Quimby 1/2018 - C.S. File 65/99-48