

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 20 and 21

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by W. S. Chapman, Deputy Surveyor, under Contract #234, dated June 24, 1875 - (DCSO records Vol. 14 Page(s) 5818)

Set post 4 ft. long, 4" dia. and 1 ft. in ground, for ¼ sec. cor., from which
A Maple 8" dia., bears N.40°E., 38 lks. dist.
A Fir 44" dia., bears S.60°W., 35 lks. dist.

BLM resurvey by James E. Jelley, Cadastral Surveyor - under Group #863, surveyed May/July 1975 - (DCSO records Vol. 38 Page(s) 15581)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

¼
S 20 | S 21
T 28 S R 8 W
1975

from which
A Fir 4" dia., bears N.86°E., 14½ lks. dist. mkd. ¼ S21 BT
A Fir 6" dia., bears S.89½°W., 26 lks. dist. mkd. ¼ S20 BT
Corner is located in bottom of descent, slopes E.

Troy Rambo - For: Seneca Jones Timber co. - Sept. 2002 (added 5/2011) - M141-11

Found - 1975 BLM brass cap
A 12 DF with a healed face - bears N.86°E., 4½ lks.
An 18 DF with a healed face - bears S.89½°W., 26 lks
New - Scribed "¼ S20 BT" on a 16 DF, bears S.36°W. 28.6 ft
Scribed "¼ S21 BT" on a 17 DF, bears S.24°E. 14.1 ft.

BLM Retracement by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2300, Surveyed Sept/Oct. 2009 - (DCSO records Vol. 56 Page(s) 22272-3)

The ¼ sec. cor. of secs. 20 and 21 established by Chapman in 1875, reestablished by Jelley in 1975, perpetuated by Troy J. Rambo, in 2002, monumented with an iron post, 2½" dia., firmly set, projecting 2" above ground, with brass cap (properly) mkd.

from which BTs mkd. by Jelley, reported by Jelley and Rogers
A fir, 11" dia.. bears N.86°E., 9.6 ft., with a healed blaze.
A fir, 20" dia., bears S.89½°W., 17.2 ft., with a healed blaze.
continued next page

TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 300340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 20 and 21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and bearing trees mkd. by Rambo
A fir, 18" dia., bears S.26 $\frac{3}{4}$ °E.. 4.2 ft. to spike at right side base, with a healed blaze.
A fir, 18" dia., bears S.38 $\frac{1}{4}$ °W.. 28.5 ft. to spike at right side base, with a healed blaze.