

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4, 5, 8 and 9

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by W. S. Chapman, Deputy Surveyor, under Contract #234, dated June 24, 1875 - (DCSO records Vol. 14 Page(s) 5820-21)

On SE. slope of hill, set post 4 ft. long, 5" dia., 1 ft. in ground, for corner of secs. 4, 5, 8 and 9, from which
A Fir 36" dia., bears N.70°W., 97 lks. dist.
A Fir 12" dia., bears S.50°W., 77 lks. dist.
A Fir 30" dia., bears S.60°E., 68 lks. dist.
A Laurel 3" dia., bears N.40°E., 33 lks. dist.

Survey by Marvin C. Ramsey - For: Southern Oregon Plywood - July/Aug., 1962 - C.S. File 51/242

Determined by double proportion. Find no evidence of orig. sec. corner.
Set Iron pipe 3 ft. long, 2" dia., 28" in the ground mkd. RS404, from which new bearing trees:
8" D.Fir bears N.18°E., 10 lks. dist. mkd. T28S R8W S4 RS404 BT.
8" D.Fir bears S.44°E., 18 lks. dist. mkd. T28S R8W S9 RS404 BT.
10" D.Fir bears S.26°W., 3 lks. dist. mkd. T28S R8W S8 RS404 BT.
18" D.Fir bears N.31°W., 56 lks. dist. mkd. T28S R8W S5 RS404 BT.

BLM resurvey by James E. Jelley, Cadastral Surveyor - under Group #863, surveyed May/July 1975 - (DCSO records Vol. 38 Page(s) 15587)

Point for the sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:
T 28 S R 8 W
S 5 S 4
S 8 S 9
1975

from which
A Fir 10" dia., bears N.14°E., 117 lks. dist. mkd. T28S R8W S4 BT.
A Fir 8" dia., bears S.14°E., 54½ lks. dist. mkd. T28S R8W S9 BT.
A Fir 10" dia., bears S.50½°W., 51 lks. dist. mkd. T28S R8W S8 BT.
A Fir 10" dia., bears N.3°W., 30½ lks. dist. mkd. T28S R8W S5 BT.

(Cont. Next Page)

TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 300600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4, 5, 8 and 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

From this point, a local corner, established by Ramsey in 1962, bears N.62°42'E., 0.916 chs. dist., monumented with an iron pipe, 2" dia., firmly set, projecting 4" above ground, from which bearing trees mkd. by Ramsey:

- A Fir 10" dia., bears N.18°E., 10 lks. dist., with healed blaze.
- A Fir 11" dia., bears S.44°E., 18 lks. dist., with healed blaze.
- A Fir 13" dia., bears S.26°W., 3 lks. dist., with healed blaze.
- A Fir 22" dia., bears N.31°W., 56 lks. dist., with healed blaze.

Cor. Fd. and Used in BLM resurvey by Boyd W. Peterson, under Group #1364, Surveyed May/Aug. 1987 - (DCSO records Vol. 48 Page(s) 18402)