TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 300640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 4 and 5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by George S. Pershin, under Contract #238, Dated, July 13, 1875 - (DCSO records Vol. 14 Page(s) 5828)

Set Fir post for ¼ sec. cor., from which
A Fir 6" dia., bears N.47°E., 22 lks. dist.
A Fir 10" dia., bears S.42°W., 95 lks. dist.

Survey by Marvin C. Ramsey - For: Southern Oregon Plywood - July/Aug. 1962 - C.S. File 51/242

38.99 chains - Point for the ¼ sec. cor. at proportionate distance. Find no evidence of the original corner.
Set Iron pipe 3 ft. long, 1½" dia., 28" in the ground mkd. RS404, from which
D.Fir 24" dia., bears S.11°E., 16 lks. mkd. ¼ S4 RS404 BT.
D.Fir 12" dia., bears N.82°W., 12 lks. mkd. ¼ S5 Rs404 BT.

BLM resurvey by James E. Jelley, Cadastral Surveyor - under Group #863, surveyed May/July 1975 - (DCSO records Vol. 38 Page(s) 15590)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

¼
S 5 S 4
T 28 S R 8 W
1975

from which
A Fir 18" dia., bears S.56°E., 35 lks. dist. mkd. ¼ S4 BT
A Fir 15" dia., bears S.85½°W., 29 lks. dist. mkd. ¼ S5 BT

From this point, a local corner, established by Ramsey in 1962, bears N.24°34'E., 0.847 chs. dist., monumented with an iron pipe, 1½" dia., firmly set, projecting 4" above ground, from which bearing trees mkd. by Ramsey:
A Fir 25" dia., bears S.11°E., 16 lks. dist., with healed blaze.
A Fir 14" dia., bears N.82°W., 12 lks. dist., with healed blaze.

Fd. OK, Dec. 1986 by R. Hintz - M 103-8