

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 28

Alias	Description

Donald Bentz, LS #839 - For: Superior Lumber Co. - Aug. 1993
- M 117-61

Set 5/8" x 30" Iron rod with cap mkd. "i.e. Engineering, from which

16" Hemlock bears N.62°E., 18.65 ft., (found blazed as a corner tree)

14" Hemlock bears S.70½°E., 9.2 ft.

10" Fir bears S.70°W., 2.5 ft.

8" Fir bears N.14°W., 24.2 ft.

All trees scribed with BT tags.

Found OK by D. Edwards, Jan. 2003 - M141-66
FD. BC & 4 BTs, by K. Hoffine - 1/2009 - M158-54

Mark Smalley, Roseburg Forest Products - Party Chief: William Olson - May 2009 - C.S. File 65/66-28

Found - IR with Yellow plastic cap "i.e. Engineering"
16" Hemlock N.62°E., 18.95' Snag with visible scribe 1993

13" Hemlock S.70½°E., 9.2' Healed face (rec 14" hemlock) 1993

11" Fir S.70½°W 2.5' Snag with healed face 1993

9" Fir N.14°W., 24.2' Snag with healed face 1993

New - 28" Douglas fir S.52°W., 39.4' measured to nail in the side-center of stump Scribed "C¼BT" with LS 2354 brass washer

24" Douglas fir S.76°W., 46.5' measured to nail in the side-center of stump Scribed "C¼BT" with LS 2354 brass washer

No other suitable trees available

Note - Compass decl. 18°E.