

TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 340340

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 21

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM resurvey by James E. Jelley and Wayne L. Rogers,
Cadastral Surveyors, under Group #1028, surveyed Oct.
1980/May 1984 - (DCSO records Vol. 45 Page(s) 17396)

Point for the center 1/4 sec. cor. of sec. 21, at
intersection with the E. and W. center line.
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground,
with brass cap mkd: T 28 S R 8 W
C 1/4 S 21
1980

from which

- A Cedar 8" dia., bears N.22°E., 13 lks. dist. mkd. C ¼ S21
BT.
- A Fir 6" dia., bears S.36¼°W., 22 lks. dist., mkd. C ¼ S21
BT.

Tony Hostetter - For: Weyerhaeuser Co. - Jan. 2019 - C.S.
File 65/103-4

Found - 1980 BLM brass cap as described. From which:
18" Cedar, face evident, bears; N.22°E., 8.6 ft to
center.
New BTs- 12" Fir, mkd "X", BT tag, S.54°E., 16.3 ft to spike.
12" Fir, mkd "X", BT tag, S.32°E., 16.0 ft to spike.
6" Cedar, mkd "X", BT tag, N.48°E., 5.9 ft to spike.