

TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 340500

PRIMARY CORNER DESCRIPTION 1/4 cor. for secs. 9 and 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by W. S. Chapman, Deputy Surveyor, under Contract #234, dated June 24, 1875 - (DCSO records Vol. 14 Page(s) 5820)

Set post 4 ft. long, 4" dia., 1 ft. in ground for ¼ sec. cor., from which
A Fir 40' dia., bears S.32°E., 10 lks. dist.
A Fir 10" dia., bears N.41½°W., 27 lks. dist.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; J. Fee, crew - July/Aug. 1957 - C.S. File 49/5-10

Found recently cut wooden stake at corner, from which
A 48" Fir snag, bears S.32°E., 6.6 ft., old but very legible bark scribing reads "¼ S BT"
A 24" Hemlock with good scar facing corner bears N.41½°W., 17.8 ft.

Find newly blazed and scribed trees:
12" Yew N.22°W., 29.7 ft. scribed ¼ S9 BT.
24" W.Fir S.50°E., 53.7 ft. scribed ¼ S16 BT.
Yellow tags on both new BTs were signed "L.V. Olson" May 1957
R.H. Gee's business card was tacked on the Yew BT.
At corner, SET Iron pipe with brass cap stamped:

County Surveyors Office
T 28 S R 8 W
¼ $\frac{S \ 9}{S \ 16}$
1957

Cor. Fd. and used in BLM Resurvey by Lynn Roseberry; Daniel Berry; Gordon Popken and Albert Garrison, Cadastral Surveyors, under Group #'s 691 and 764, Surveyed June, 1969/April 1973 - (DCSO records Vol. 36 Page(s) 15085)

Cor. Fd. and used in BLM resurvey by Boyd W. Peterson, under Group #1364, Surveyed May/Aug. 1987 - (DCSO records Vol. 48 Page(s) 18407)

Fd. OK, July 1993 by D. Bentz - M 112-80