

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 4 and 9

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by W. S. Chapman, Deputy Surveyor, under Contract #234, dated June 24, 1875 - (DCSO records Vol. 14 Page(s) 5821)

Set post 4 ft. long, 4" dia., and 1 ft. in ground for sec. cor., from which
A Laurel 15" dia., bears N.40°W., 34 lks. dist.
A Fir 15" dia., bears S.35°W., 35 lks. dist.

Survey by Marvin C. Ramsey - For: Southern Oregon Plywood - July/Aug. 1962 - C.S. File 51/242

40.84 chains-Point for the 1/4 sec.cor. at proportionate dist. Find no evidence of the original corner.
Set Iron pipe 3 ft. long, 1 1/2" dia. 28" in the ground, mkd. RS404, from which
18" D.Fir bears N.57°E., 8 lks. mkd. 1/4 S4 RS404 BT.
10" D.Fir bears S.53°W., 9 lks. mkd. 1/4 S9 RS404 BT.

BLM resurvey by James E. Jelley, Cadastral Surveyor - under Group #863, surveyed May/July 1975 - (DCSO records Vol. 38 Page(s) 15588-89)

Point for the 1/4 sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:
1/4 $\frac{S\ 4}{S\ 9}$
T 28 S R 8 W
1975

from which
A Fir 17" dia., bears N.44°E., 17 lks. dist. mkd. 1/4 S4 BT
A Fir 13" dia., bears S.50 1/2°E., 32 lks. dist. mkd. 1/4 S9 BT

From this point, a local corner, established by Ramsey in 1962, bears N.73°03'E., 0.72 chs. dist., monumented with an iron pipe, 1 1/2" dia., firmly set, projecting 2" above ground, from which bearing trees mkd. by Ramsey:
A Fir 20" dia., bears N.57°E., 8 lks. dist. with healed blaze.
A Fir 13" dia., bears S.53°W., 9 lks. dist. with healed blaze.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 4 and 9

Alias	Description
Alias	Description
Alias	Description
Alias	Description

BLM resurvey by Boyd W. Peterson, under Group #1364, Surveyed May/Aug. 1987 - (DCSO records Vol. 48 Page(s) 18401-02)

Point for the ¼ sec. cor. of secs. 4 and 9, at proportionate distance; there is no remaining evidence of the original corner.

From this point, the ¼ sec. cor., erroneously reestablished by Jelley in 1975, bears S.89°34'W., 0.67 chs. dist., monumented with an iron post, 2½" dia., set, marked, and witnessed as described in the official record. Remove the iron post, destroy the marks on the bearing trees, and at the true corner point

RESET the iron post 28" long, 2½" dia., 24" in the ground with brass cap mkd:

$\frac{1}{4}$ S 4
S 9
T 28 S R 8 W
1975
1987

from which

- A Fir 17" dia., bears S.17¼°W., 43 lks. dist. mkd. ¼ S9 BT
- A Fir 11" dia., bears N.60½°W., 24 lks. dist. mkd. X BT.

From this same point, a local corner established by Ramsey in 1962, bears N.1°44'W., 0.20 chs. dist., monumented with an iron pipe, 1½" dia., firmly set, projecting 6" above ground from which bearing trees mkd. by Ramsey:

- A Fir 21" dia., bears N.57°E., 8 lks. dist. with healed blaze.
- A Fir 13" dia., bears S.53°W., 9 lks. dist. with healed blaze.