TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 400140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 33 and 34

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 14 Page(s) 5806)

Set ¼ sec. post, from which
A Laurel 9" dia., bears N.75°W., 9 lks. dist.
A Laurel 9" dia., bears S.55°E., 12 lks. dist.

BLM resurvey by James E. Jelley, Cadastral Surveyor - under Group #863, surveyed May/July 1975 - (DCSO records Vol. 38 Page(s) 15573)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd: ¼
S 33|S 34
T 28 S R 8 W
1975
from which
A Cedar 12" dia., bears S.38¼°E., 62 lks. dist., mkd. ¼ S34 BT.
A Fir 13" dia., bears N.11½°W., 45½ lks. dist., mkd. ¼ S33 BT.

Ron Quimby - J Leonard & J Laub - 4/2012 - C.S. File 65/76-39

Found - BLM brass cap, good condition.
24" cedar S.38¼°E., 40.9 ft. good scar.
New - 14" Cedar N.34°W., 16.7 ft. scribed ¼ S33 BT
19" D.Fir N.79°E., 8.8 ft. scribed ¼ S34 BT
11" D.Fir S.50°W., 24.3 ft. scribed ¼ S33 BT