

PRIMARY CORNER DESCRIPTION Sec. Cor. for 27, 28, 33 and 34

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 14 Page(s) 5806-07)

-
- Set post cor. secs. 27, 28, 33 and 34, from which
- A Fir 24" dia., bears N.85°W., 57 lks. dist.
 - A Fir 10" dia., bears S.85°E., 53 lks. dist.
 - A Fir 9" dia., bears S.75°W., 58 lks. dist.
 - A Fir 9" dia., bears N.80°E., 90 lks. dist.

BLM resurvey by James E. Jelley, Cadastral Surveyor - under Group #863, surveyed May/July 1975 - (DCSO records Vol. 38 Page(s) 15574)

The Sec. Cor., determined at record bearing and distance from the remains of the original bearing trees:

- A sawed Fir stump 28" dia., bears S.85°E., 53 lks. dist., with scribe marks BT visible on opened lower blaze.
- A Fir root crown 35" dia., bears N.85°W., 57 lks. dist., with a down Fir alongside, no marks visible.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 28 S R 8 W
<u>S 28 S 27</u>
S 33 S 34
1975

from which new bearing trees

- A W.Fir 5" dia., bears N.67½°E., 4 lks. dist. mkd. T28S R8W S27 BT.
- A Fir 6" dia., bears S.38½°E., 22½ lks. dist., mkd. T28S R8W S34 BT.
- A Hemlock 8" dia., bears S.30 3/4°W., 34½ lks. dist., mkd. T28S R8W S33 BT.
- A W.Fir 6" dia., bears N.83°W., 38 lks. dist., mkd. T28S R8W S28 BT.

David Edwards - For: Roseburg Resources - 1/2003 - M 141-66

Found - Brass cap

- 9" Fir bears S.38½°E., 14.9'
- 12" Hemlock S.30¾°W., 22.8'

- New BTs-
- 5" Fir N.16°E., 17.7' "S27 BT"
 - 6" Fir N.4°W., 16.62' "S28 BT"

FD. Ok by R. Quimby, 4/2012 - C.S. File 65/76-38