

PRIMARY CORNER DESCRIPTION Sec. Cor. for 15, 16, 21 and 22

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 14 Page(s) 5809)

-----

Set post, cor. secs. 15, 16, 21 and 22, from which

- A Fir 9" dia., bears S.45°W., 54 lks. dist.
- A Fir 12" dia., bears N.70°W., 37 lks. dist.
- A Fir 10" dia., bears N.20°W., 89 lks. dist.
- A Fir 30" dia., bears S.62°E., 50 lks. dist.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; J. Fee, crew - July/Aug. 1957 - C.S. File 49/5-1

-----

Found - Orig. SE. BT, now 36" snag. This tree was bark scribed. Bark with scribing "R 8" laying on ground at base of tree.

I find evidence of Fir tree at record dist. & brg. for SW. original BT.

I can find no evidence of NE. orig. BT., nor SW. orig. BT. (which would fall in cat road)

Set Brass cap at cor. mkd: County Surveyors Office

T 28 S R 8 W
S 16   S 15
S 21   S 22
1957

from which:

- 14" W.Fir bears N.82°W., 46.7 ft. scribed T28S R8W CS BT.
- 30" R.Fir bears S.47°W., 39.0 ft. scribed S21 T28S R8W CS BT.
- 15" W.Fir bears N.86°W., 42.0 ft. scribed S16 T28S R8W CS BT. (This tree damaged severely, will probably die)
- 10" R.Fir bears N.73°E., 60.0 ft. scribed S15 T28S R8W CS BT.
- 26" Hemlock bears S.2½°E., 39.5 ft. scribed S22 T28S R8W CS BT.

Fd. BC & 4 BTS B Shaner - 4/1972 - M42-66

BLM Resurvey by Lynn Roseberry; Daniel Berry; Gordon Popken and Albert Garrison, Cadastral Surveyors, under Group #'s 691 and 764, Surveyed June, 1969/April 1973 - (DCSO records Vol. 36 Page(s) 15077-78)

-----

The Sec. Cor., perpetuated and recorded by Byron in 1957, monumented with an iron post 1½" dia., firmly set, protruding 8" above ground with brass cap mkd. in 1957 (Cont. Next Pg)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 15, 16, 21 and 22

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

from which the remains of the original bearing tree  
A root hole bears S.62°E., 50 lks. dist. with a down and  
decayed Fir alongside, no marks visible.  
and bearing trees mkd. by Byron  
A Fir 17" dia., bears N.73°E., 87½ lks. dist., with healed  
double blaze.  
A Hemlock 26" dia., bears S.2½°E., 60 lks. dist. with  
healed double blaze.  
A Fir 30" dia., bears S.45°W., 62 lks. dist., with healed  
blaze.  
A sawed White Fir stump 15" dia., bears N.86°W., 64 lks.  
dist., no marks visible.  
A Fir snag 14" dia., bears N.83½°W., 71 lks. dist., with  
healed double blaze.  
and a bearing tree mkd. by Roseberry in 1969:  
A Fir 20" dia., bears N.57°W., 141 lks. dist., with scribe  
marks T28S R8W S16 BT visible on partially healed  
blaze.

Cor. Fd. and Used in BLM resurvey by James E. Jelley,  
Cadastral Surveyor - under Group #863, surveyed May/July  
1975 - (DCSO records Vol. 38 Page(s) 15583-84)

BLM resurvey by Boyd W. Peterson, under Group #1364, Surveyed  
May/Aug. 1987 - (DCSO records Vol. 48 Page(s) 18404)  
-----  
The Sec. Cor., monumented with an iron post 1¼" dia., firmly  
set, projecting 6" above ground with brass cap mkd. in 1957  
from which the remains of bearing trees mkd. by Byron in 1957  
A Fir 25" dia., bears N.73°E., 87½ lks. dist., with healed  
double blaze.  
A Hemlock snag 26" dia., bears S.3 3/4°E., 60 lks. dist.,  
with fragmentary scribing visible on partially healed  
blaze.  
A sawed Fir stump 30" dia., bears S.45°W., 62 lks. dist.,  
no marks visible.  
and new bearing trees:  
A Fir 6" dia., bears S.52°E., 15 lks. dist., mkd. T28S R8W  
S22 BT.  
A Fir 4" dia., bears S.57°W., 20½ lks. dist. mkd. X BT.  
A Fir 5" dia., bears N.69½°W., 30 lks. dist. mkd. T28S R8W  
S16 BT.

Fd. OK, June 1993 - M 117-37

continued next page

PRIMARY CORNER DESCRIPTION Sec. Cor. for 15, 16, 21 and 22

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

BLM Retracement by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2300, Surveyed Sept/Oct. 2009 - (DCS0 records Vol. 56 Page(s) 22272-3)

-----  
The cor. of secs. 15, 16, 21, and 22, established by Hathorn in 1856, perpetuated from original evidence no longer existence by Byron, in 1957, monumented with an iron post, 1¼" dia., firmly set, projecting 7" above ground, with brass cap (properly) mkd. from which the remains of BTs mkd. by Byron, reported by Peterson

A fir. 32" dia., bears N.73°E., 57.8 ft., with a healed blaze.

A roothole bears S.3¾°E., 39.6 ft., downhill of which is a hemlock snag, size indeterminate, with no marks visible on a hollowed blaze.

A sawed fir stump, 28" dia., bears S.45°W., 40.9 ft., with no marks visible and a metal cover.

and remaining BTs mkd. by Peterson

A fir, 10" dia., bears S.57°W., 13.5 ft., with a healed double blaze.

A fir, 13" dia., bears N.69½°W., 19.8 ft., with a healed blaze.

and a new bearing tree

A fir, 10 ins. diam., bears S.7½°E., 19.7 ft., mkd. T28S R8W S22 BT.

Daniel A Renton, Minister-Glaeser Surveying - Garrett Finch & Crew - For: US Department of Interior, BLM - Reston Pieces-Task 1 -June 2023 - M185-4 A-C

-----  
Found - 2½" County Surveyors Office brass cap (properly mkd), 0.5' above ground from which:

A Fir 17" dia., bears N.71°W., 19.7' with healed blaze and BT sign (1987)

A Fir 14" dia., bears S.57°W., 13.7' with 2 healed blazes and BT sign (1987)

A stump 27" dia., bears S.45°W., 40.6' with tin top and BT sign (1957)

A Fir 13" dia., bears S.7½°E., 19.7' with healed blaze and BT sign (2009)

A Fir 36" dia., bears N.73°E., 56.7' with healed blaze and BT sign (1957)

A rotted stump 18" dia., bears S.2½°E., 39.3' (1957)

(Set chaining nail at side center, BT signs on front and back, and painted red band for existing BTs)

