

TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 400440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 15 and 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 14 Page(s) 5810)

Set ¼ sec. post, from which
A Laurel 15" dia., bears N.35°E., 14 lks. dist.
A Laurel 12" dia., bears S.60°W., 22 lks. dist.

BLM Resurvey by Lynn Roseberry; Daniel Berry; Gordon Popken and Albert Garrison, Cadastral Surveyors, under Group #'s 691 and 764, Surveyed June, 1969/April 1973 - (DCSO records Vol. 36 Page(s) 15078)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 28 S R 8 W
1/4
S 16 | S 15
1969

from which
A Fir 10" dia., bears N.32½°E., 40 lks. dist. mkd. ¼ S15 BT.
A Chinquapin 12" dia., bears N.15 3/4°W., 47 lks. dist. mkd. ¼ S16 BT.

Fd. BC & 2 BTS B Shaner - 4/1972 - M42-66

Fd. and used in BLM resurvey by Boyd W. Peterson, under Group #1364, Surveyed May/Aug. 1987 - (DCSO records Vol. 48 Page(s) 18413)

Fd. OK, July 1993 by D. Bentz - M 112-80

Daniel A Renton, Minister-Glaeser Surveying - Garrett Finch & Crew - For: US Department of Interior, BLM - Reston Pieces-Task 1 - June 2023 - M185-4 A-C

Found - 3¼" BLM brass cap (properly mkd), 0.4' above ground from which:
A stump (2 ft high) 22" dia., bears N.32½°E., 26.8' with healed blaze (1973)
A Madrone 15" dia., bears S.77°E., 17.0' mkd: X W ¼ S15 BT (no record)
A Madrone 24" dia., bears N.60°E., 49.6' mkd: W ¼ S15 BT (no record)

continued next page

TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 400440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 15 and 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Chinquapin 13" dia., bears S.04°E., 24.6' mkd: W $\frac{1}{4}$ S15 BT (no record)
A stump (1ft high) 15" dia., bears N.15 $\frac{3}{4}$ °W., 31.2' with healed blaze (1973)
Established the following -
A Hemlock 22" dia., bears S.85°W., 35.2' mkd: $\frac{1}{4}$ S16 BT.
(Set chaining nail at side center, BT signs on front and back, and painted red band for existing & new BTs)