

PRIMARY CORNER DESCRIPTION Sec Cor for 3, 4, 9 and 10

Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W. S. Chapman, Deputy Surveyor, under Contract #234, dated June 24, 1875 - (DCSO records Vol. 14 Page(s) 5815)

-----  
 Set post 4 ft. long, 5" dia., and one ft. in ground, for cor. of secs. 3, 4, 9 and 10, from which  
 Fir 30" dia., bears S.4¼°E., 22 lks. dist.  
 W.Fir 15" dia., bears S.81°W., 46 lks. dist.  
 Fir 30" dia., bears N.52°W., 50 lks. dist.  
 Fir 30" dia., bears N.53°E., 68 lks. dist.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; C. Putnam, crew - June 1961 - C.S. File 52/79-11

-----  
 Found - Orig. 30" now 36" Fir, snag, N.53°E., 44.9 ft., shows good bark scribing "T28S R8W S3 B"  
 Orig. 30" now down Fir, N.52°W., 33.0 ft., bark gone  
 Orig. SW. BT, not found.  
 Orig. 30" now 40" Fir, S.4½°E., 14.5 ft., shows good bark scribing "B".

Set Brass cap at cor. mkd: County Surveyors Office  
 T 28 S R 8 W  
 S 4 | S 3  
 S 9 | S10  
 1961

New BTs- 28" Hemlock bears N.81½°W., 31.8 ft. scribed S4 T28S R8W CS BT.  
 10" Fir bears S.15½°E., 18.1 ft. scribed S10 T28S R8W CS BT.  
 12" Hemlock bears S.46°W., 62.1 ft. scribed S9 T28S R8W CS BT.  
 12" Hemlock bears N.60°E., 63.4 ft. scribed S3 T28S R8W CS BT.

Cor. Fd. and used in BLM Resurvey by Lynn Roseberry; Daniel Berry; Gordon Popken and Albert Garrison, Cadastral Surveyors, under Group #'s 691 and 764, Surveyed June, 1969/April 1973 - (DCSO records Vol. 36 Page(s) 15082)

BLM resurvey by James E. Jelley, Cadastral Surveyor - under Group #863, surveyed May/July 1975 - (DCSO records Vol. 38 Page(s) 15587-88)

-----  
 The Sec. Cor., perpetuated and recorded by Byron n 1961, monumented with an iron post 1½' dia., firmly sset, projecting 10" above ground, with brass cap mkd. in 1961 from which the remains of the original bearing trees:  
 (Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec Cor for 3, 4, 9 and 10

Alias	Description
Alias	Description
Alias	Description
Alias	Description

A Fir stump 32" dia., bears N.53°E., 70 lks. dist., with scribe marks 28S R8W S3 visible on bark blaze.  
A Fir stump 45" dia., bears S.4¼°E., 22 lks. dist., no marks visible.  
and the remains of bearing trees mkd. by Byron:  
A Hemlock 15" dia., bears N.57°E., 96 lks. dist., with healed blaze.  
A Fir stump 12" dia., bears S.15½°E., 28 lks. dist., with fragmentary scribe marks visible on open blaze.  
A Hemlock 13" dia., bears S.44°W., 96 lks. dist., with scribe marks 8S R8W CS B visible on open blaze.  
A Hemlock 36" dia., bears N.84°W., 48 lks. dist., with scribe marks T28S R8W S4 CS BT visible on open blaze.  
and a new bearing tree:  
A Fir 20" dia., bears S.40¼°E., 201 lks. dist., mkd. T28S R8W S10 BT.

Fd. OK, Dec. 1986 by R. Hintz - M 103-8

BLM resurvey by Boyd W. Peterson, under Group #1364, Surveyed May/Aug. 1987 - (DCSO records Vol. 48 Page(s) 18400)  
-----  
The Sec. Cor., monumented with an iron post 1¼" dia., firmly set, projecting 6" above ground, with brass cap mkd. in 1961 from which the remains of original bearing trees:  
A sawed Fir stump 32" dia., bears N.53°E., 70 lks. dist., no marks visible.  
A sawed Fir stump 45" dia., bears S.4¼°E., 22 lks. dist., no marks visible.  
and the remains of bearing trees mkd. by Byron:  
A Hemlock 21" dia., bears N.59°E., 96 lks. dist., with healed blaze. (Rec. N.57°E.)  
A sawed Fir stump 12" dia., bears S.15½°E., 28 lks. dist., with fragmentary scribe marks visible on partially healed blaze.  
A root hole bears S.46½°W., 96 lks. dist., with down Hemlock alongside, 14" dia., with fragmentary scribing visible on partially healed blaze. (Rec. S.44°W.)  
A sawed Hemlock stump 38" dia., bears N.84°W., 48 lks. dist., with fragmentary scribe marks visible on partially healed blaze.  
and a bearing tree mkd. by Jelley:  
A Fir 21" dia., bears S.40¼°E., 201 lks. dist. with healed blaze.  
and new bearing trees:  
  
(Cont. Next Page)

TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 400600

PRIMARY CORNER DESCRIPTION Sec Cor for 3, 4, 9 and 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Chinquapin 6" dia., bears S.72½°W., 37 lks. dist., bark scribed T28S R8W S9 BT.  
A Hemlock 4" dia., bears N.35¼°W., 20½ lks. dist. mkd. X BT.

FD ok by DCSO 11/6/2018, SJF & JL C.S. File 67/45-28