

TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 440100

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 34; & 3, T29-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 14 Pg 5794)

-----  
Set ¼ sec. post, from which  
A Fir 24" dia., bears North, 33 lks. dist.  
A Fir 20" dia., bears S.22°E., 26 lks. dist.

-----  
Douglas County Surveyors Office - Vernon "Ray" Tracy and crew  
Jan. 1969 - C.S. File 54/80 and M 37-25

-----  
Set Brass cap for ¼ corner at proportional point midway  
between section corners, mkd: County Surveyors Office  
T28S R8W ¼  $\frac{S\ 34}{S\ 3}$   
T29S  
1969

New BTs- 14" D.Fir N.72°E., 89.2 ft. mkd. ¼ S34 CS BT.  
12" D.Fir S.64°E., 65.1 ft. mkd. ¼ S3 CS BT.  
No trace of original BTs. This corner lies between old cat  
logging roads on moderate SE. slope approx. 400 ft. West of  
Nuns Creek.

-----  
Douglas Co. Surveyors Office - Randall Smith & Stephen Flause  
- Sept. 17, 1997 - C.S. 64/78-3

-----  
Found - 2½" Brass cap on a 1½" OD iron pipe protrudes 11"  
above ground (1969).  
14" now 23" dia. D.Fir, with a fully healed double  
blaze, bears N.66 ¾°E., 89.2' agrees with BT  
tag by Shaner 6/72 (rec. per 1969 DCSO N.72°E.,  
89.2')  
12" now 23" dia. D.Fir, with a fully healed double  
blaze, bears S.64°E., 64.1' (rec S.64°E. 65.1')  
10" B.Oak no blazes visible with a 1972 Shaner  
line tag, bears S.73°E., 5.2' agrees with tag  
we double blaze and scribe "¼ S3 CS BT".  
New - 13" dia. D.Fir, double blazed and scribed "¼ S34  
CS BT", bears N.26°W., 20.8'.

-----  
Ron Quimby - J Leonard & J Laub - 4/2012 - C.S. File 65/76-41

-----  
Found - DCSO brass cap  
28" D.Fir S.64°E., 64.1 ft. healed face.  
10" Oak S.73°E., 5.2 ft.  
14" Fir N.26°W., 20.8 ft. vis. scribes ¼ S34 CS BT.  
Down 24" Fir N.72°E., 89.2 ft. (Shaner Tag)  
New - 10" D.Fir S.89°W., 67.1 ft. scribed S ¼ BT.