

TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 440200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 27 and 34

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 14 Page(s) 5807)

Set ¼ sec. post, from which
A Fir 40" dia., bears N.30°E., 6 lks. dist.
A Laurel 12" dia., bears S.60°W., 64 lks. dist.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; J. Fee, crew - July/Aug. 1957 - C.S. File 49/5-14

Found - Orig. NE. BT now 50" Fir, bark scribed ¼ S.
Also found stump hole and parts of old Laurel at record bearing and distance of orig. SW. BT.
Set Brass cap at cor. mkd: County Surveyors Office
T 28 S R 8 W
¼ $\frac{S\ 27}{S\ 34}$
1957

New BTs- Rescribed orig. NE. BT, bark scribed, "S27 ¼ CS BT", bears N.30°E., 6.0 ft. (dist. to center of BT)
22" Cedar S.59°W., 60.2 ft. "¼ S34 CS BT".

Cor. Fd. and Used in BLM resurvey by James E. Jelley, Cadastral Surveyor - under Group #863, surveyed May/July 1975 - (DCSO records Vol. 38 Page(s) 15574-75)

Ron Quimby - J Leonard & J Laub - 4/2012 - C.S. File 65/76-42

Found - DCSO brass cap
48" D.Fir N.30°E., 6.0 ft. bark scribed.
36" cedar S.59°W., 60.2 ft. good scar.
14" madrona (slid downhill)
New - 12" madrona N.60°E., 28.6 ft. scribed ¼ S27 BT.
48" D.Fir N.38°W., 32.3 ft. scribe ¼ S27 BT.