

TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 440300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 22 and 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 14 Page(s) 5808)

-----  
Set ¼ sec. post, from which  
A Fir 24" dia., bears N.25°E., 5 lks. dist.  
A Fir 12" dia., bears S.13°E., 5 lks. dist.

BLM Resurvey by Lynn Roseberry; Daniel Berry; Gordon Popken and Albert Garrison, Cadastral Surveyors, under Group #'s 691 and 764, Surveyed June, 1969/April 1973 - (DCSO records Vol. 36 Page(s) 15076)

-----  
Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.  
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T28S R8W  
¼  $\frac{S\ 22}{S\ 27}$   
1973

from which  
A Fir 11" dia., bears N.5½°E., 29 lks. dist. mkd. ¼ S22 BT  
A Fir 8" dia., bears S.38°W., 21 lks. dist. mkd. ¼ S27 BT.

Fd. and used in sec. subd. survey by BLM Resurvey by Dale T. Bedell, Cadastral Surveyor, under Group #1278, Surveyed July/Oct. 1985 - (DCSO records Vol. 48 Page(s) 18260)