

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 22

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

N. E. Britt, Co. Surveyor - July 16-17, 1880 - Vol. 1 Pg. 82

Set at the intersection of the N-S and E-W centerlines of section 22.

Corner point is a rock in place, 4 ft. by 4 ft., protruding 4 ft. above the ground, from which

A Chinquapin 10" bears N.0°10'E., 162 lks.

BLM Resurvey by Dale T. Bedell, Cadastral Surveyor, under Group #1278, Surveyed July/Oct. 1985 - (DCSO records Vol. 48 Page(s) 18261)

The center ¼ sec. cor. of sec. 22, established and recorded by Britt in 1880, and is accepted as the corner, monumented with a sandstone, 4 x 4 ft., projecting 4 ft. above ground, no marks visible.

At the corner point

Set a brass tablet 3¼" dia., with a 3½" stem in a drill hole in the top center of the corner stone mkd. T 28 S R 8 W

C ¼
S 22
1985

from which

An Alder 10" dia., bears S.78°E., 33 lks. dist., bark scribed C¼ S22 BT.

A Cedar 18" dia., bears N.76°W., 32 lks. dist., mkd. C¼ S22 BT.

Fd. OK, July 1993 by M. Heimbürger - M 117-37