

TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 440500

PRIMARY CORNER DESCRIPTION 1/4 cor. for Secs. 10 and 15

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 14 Page(s) 5810)

Set ¼ sec. post, from which
A Laurel 12" dia., bears S.71°E., 19 lks. dist.
A Fir 7" dia., bears N.79°E., 28 lks. dist.

BLM Resurvey by Lynn Roseberry; Daniel Berry; Gordon Popken and Albert Garrison, Cadastral Surveyors, under Group #'s 691 and 764, Surveyed June, 1969/April 1973 - (DCSO records Vol. 36 Page(s) 15080)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 28 S R 8 W

¼ $\frac{S 10}{S 15}$

1969

from which
A Fir 7" dia., bears N.17½°W., 48 lks. dist. mkd. ¼ S10 BT
A Chinquapin 7" dia., bears S.33°W., 16 lks. dist. mkd. ¼ S15 BT.
Corner falls 6 lks. S. of wire fence extending E. and W.

Fd. OK B Shaner - 4/1972 - M42-66
Fd. OK, Nov. 1989 by Brubaker - M 109-53

Cor. fd. and used in BLM resurvey by Boyd W. Peterson, under Group #1364, Surveyed May/Aug. 1987 - (DCSO records Vol. 48 Page(s) 18405-06)