

TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 500100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 34 & 35; 2 & 3, T29-8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 14 Page(s) 5793)

Set post cor. secs. 34, 35, 2 and 3, from which
An Oak 18" dia., bears S.75°E., 47 lks. dist.
An Oak 20" dia., bears S.62°W., 77 lks. dist.
A Fir 30" dia., bears N.53°W., 97 lks. dist.
A Fir 24" dia., bears N.62°E., 113 lks. dist.

A. Boyer - Wit: Ralph Heater - Oct. 22, 1935 - C.S. File 16/70

Renewed one tree only from corner as located from trees now in,
A 12" Red Fir S.72°W., 50.5 ft.
Original trees still in are:
A 40" Fir N.43°W., 97 lks.
A 36" Fir N.62°E., 113 lks.
A 24" oak S.75°E., 42 lks.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; J. Fee, crew - Aug. 6, 1957 - C.S. File 49/5-16

Found Boyer's BT, 1935, 12" now 14" Fir, good condition S.72°W., 50.5 ft. None of the original BTs found.
Set brass cap at corner mkd: County Surveyors Office

34	35	T28S	R8W
3	2	T29S	

1957

New BTs- 14" Fir N.2°W., 24.0 ft. scribed S34 T28S R8W CS BT
10" Fir N.17½°E., 17.2 ft. scribed S35 T28S R8W CSBT
12" Fir S.10°E., 30.5 ft. scribed S2 T29S R8W CS BT.

Wayne Rogers, Bureau of Land Management - June 1, 1989 - C.S. File 63/87 (Also in Vol. 50 Pages 18844-45)

Found - 1¼" iron post found loosely set projecting 24" above ground.
BT by Boyer, A Fir snag 17", bears S.70°W., 77 lks.
BTs by Byron:
A Fir 11" bears N.21½°E., 25 lks., healed double blaze.
A Fir 14" dia., bears S.8°E., 46 lks., healed double blaze.
A Fir 19" bears N.4¼°W., 36 lks., healed double blaze.

(Cont. Next Page)

TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 500100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 34 & 35; 2 & 3, T29-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Referenced monument and reset 28" in the ground with 8" projecting above ground.
New BT - A Fir 19" bears S.39½°W., 45 lks. mkd. T29S R8W S3 BT.

FD. Ok by R. Quimby, 4/2012 - C.S. File 65/76-38