

TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 500240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 26 and 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 14 Page(s) 5802)

Set ¼ sec. post, from which
 An Oak 10" dia., bears N.30°W., 50 lks. dist.
 An Oak 12" dia., bears S.66°E., 129 lks. dist.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; J. Fee, crew - July/Aug. 1957 - C.S. File 49/5-15

Found - Orig. 12" now 20" Oak, S.66°E., 85.1 ft. This BT has been opened several years ago. I find good scribing "¼S".

I find base of rotted stump, Oak, at record distance and bearing for NW. tree.

Set Brass cap at cor. mkd: County Surveyors Office

T 28 S R 8 W

¼ S27 | S26

1957

New BTs- 12" Laurel bears N.72°W., 12.9 ft. scribed ¼ S27 CS BT.

14" R.Fir bears N.51°E., 9.8 ft. scribed ¼ S26 CS BT