

TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 500440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 14 and 15

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 14 Page(s) 5804)

Set ¼ sec. post, from which
A W.Oak 10" dia., bears S.76°W, 50 lks. dist.
A Fir 12" dia., bears S.5°E., 22 lks. dist.

Survey by Bruce A. Shaner - For: US BLM - Aug. 24, 1972 - M 42-66

Found - Orig. 24" D.Fir BT, stump, badly rotted, scribes visible, bears S.5°E., 14.5 ft.
Set a brass cap mkd. "T28S R8W W.M 1/4 S15 S14 1972".
I scribe-12" D.Fir "¼ S S14 BT" bears S.31½°E., 42.0 ft.
16" D.Fir "¼ S S15 BT" bears West, 47.0 ft.

Fd. and used in BLM resurvey by Boyd W. Peterson, under Group #1364, Surveyed May/Aug. 1987 - (DCSO records Vol. 48 Page(s) 18411-12)

Fd. BC & accessories by R. Quimby, 4/2013 - M157-71