

TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 500540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 10 and 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 14 Page(s) 5805)

-----  
Set ¼ sec. post, from which  
A B.Oak 20" dia., bears N.69°W., 89 lks. dist.  
A B.Oak 36" dia., bears N.65°E., 215 lks. dist.

H.L. Eppstein, Co. Surveyor - Wit: Harley Johnson; B.A. Lane; G.C. Sellers - March 4, 1930 - Vol. 4 Pg. 9; C.S. File 14/58

-----  
Set a 3" x 3" x 30" Oak stake from two Oaks, Orig. BTs.  
Marked new BT:  
B.Oak 24" dia., N.26°W., 73.0 ft.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; S. Bilow, crew - Sept. 24, 1957 - C.S. File 49/5-24

-----  
Found - Eppstein's renewed BT, now 34" B.Oak, N.26°W., 73.0 ft. I open and find good scribing "BT".  
Original BTs now gone.

Set Brass cap at cor. mkd: County Surveyors Office  
T 28 S R 8 W  
¼ S10 | S11  
1957  
New BTs- I rescribe 34" B.Oak, N.26°W., 73.0 ft. "BT" only.  
Blaze and scribe 7" R.Fir N.27°E., 107.6 ft. "¼ S11 CS BT".  
Brass cap in fence corner as shown on a sketch in file.

Corner Fd. and Used in BLM Resurvey by Lynn Roseberry; Daniel Berry; Gordon Popken and Albert Garrison, Cadastral Surveyors, under Group #'s 691 and 764, Surveyed June, 1969/April 1973 - (DCSO records Vol. 36 Page(s) 15072-73)

Cor.Fd. and used in BLM Resurvey by Dale T. Bedell, Cadastral Surveyor, under Group #1278, Surveyed July/Oct. 1985 - (DCSO records Vol. 48 Page(s) 18258)

Fd. OK, March 1991 - M 111-70