

TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 540200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 26 and 35

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 14 Page(s) 5802)

-----  
Set ¼ sec. post, from which  
A Fir 40" dia., bears N.79°W., 17 lks. dist.  
A Cedar 18" dia., bears S.74°E., 30 lks. dist.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; S. Bilow, crew - Sept. 1957 - C.S. File 49/5-23

-----  
Found - Orig. 40" now 20" R.Fir, N.79°W., 11.2 ft. BT bark scribed "¼S" above. I open old face at base and find good scribing "BT".

I can find no trace of the original SE. BT.  
Set Brass cap at cor. mkd: County Surveyors Office  
T 28 S R 8 W

¼  $\frac{S\ 26}{S\ 35}$   
1957

New BTs- Rescribe (bark) original N.79°W., 11.2 ft., scribed "BT" only.

Blaze and scribe 7" Cedar S.4°W., 19.7 ft. scribed "¼ S35 CS BT"

Fd. and used in BLM resurvey by Wayne L. Rogers, Cadastral Surveyor, Group #1483, surveyed May/July 1989 - (DCSO records Vol. 50 Page(s) 18857-58)