

TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 540300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 23 and 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 14 Page 5803)

-----  
Set ¼ sec. post, from which  
A Fir 18" dia., bears N.60°W., 23 lks. dist.  
A Laurel 6" dia., bears S.55°W., 13 lks. dist.

Survey by Glenn Baughman - For: Sun Studs, Inc. - March 1973  
- M 47-76

-----  
Set Brass cap, from which  
7" W.Fir bears N.56°E., 9.9 ft.  
7" W.Fir S.30°W., 15.6 ft.

Fd. and used in BLM resurvey by James E. Jelley, Cadastral Surveyor - under Group #863, surveyed May/July 1975 - (DCSO records Vol. 38 Page(s) 15567)

Survey by Glenn Baughman - For: Larry Thomas - April 1978,  
Revised map, M 70-6

-----  
Set brass cap in 1973, reestablished July 1975, from which  
9" W.Fir bears S.50°W., 17.3 ft.  
6" W.Fir bears N.65°W., 8.9 ft.

BLM resurvey by James E. Jelley and Wayne L. Rogers, Cadastral Surveyors, under Group #1028, surveyed Oct. 1980/May 1984 - (DCSO records Vol. 45 Page(s) 17388-89)

-----  
The ¼ sec. cor., monumented with an iron post 1¼" dia., firmly set, projecting 9" above ground, with brass cap mkd.

T 28 S R 8 W

¼  $\frac{S\ 23}{S\ 26}$

RLS 536 1973

from which the remains of bearing trees mkd. by Baughman in 1973:

A Grand Fir snag 8" dia., bears S.50°W., 26 lks. dist. with fragmentary scribe marks visible on partially healed blaze.

A Grand Fir 9" dia., bears N.65°W., 13½ lks. dist. with fragmentary scribe marks visible on open blaze.

and a new bearing tree

A Madrone 16" dia., bears S.73½°E., 59 lks. dist. mkd. ¼ S26 BT on bark.

continued next page

TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 540300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 23 and 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Dan Saily, Lone Rock Timber - Crew: Brett Ragon, Ignacio Roman, Trevor Clemo & Weston Addington - 4/2023 - M182-25

-----  
Set - 2½" aluminum cap is marked: LONE ROCK TIMBER T28S R8W S23 S26 ¼ 2023 85006PLS on a 5/8" x 60" iron rod. The top of the cap is 0.25 ft above ground. We set a galvanized iron post 1 ft north.

New - 14" D.Fir bears S.47°W., 26.1 ft scribed ¼ S26 BT and tagged

13" D.Fir bears N.86¼°E., 18.9 ft scribed ¼ S23 BT and tagged.

5/8"x40" iron rod with orange plastic cap marked: LONE ROCK TIMBER 85006PLS bears S.6°01'55"W., 41.93 ft with galvanized steel post set 1 ft north

5/8"x40" iron rod with orange plastic cap marked: LONE ROCK TIMBER 85006PLS bears N.61°32'17"W., 47.29 ft with galvanized steel post set 1 ft north

Found Baughman's brass cap and iron pipe leaning out of position. We straightened at position bears N.31°08'20"W., 20.23 ft.