TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 540400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 14 and 23

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 14 Page(s) 5804)

Set ¼ sec. post, from which
A Laurel 15" dia., bears N.15°E., 40 lks. dist.
A B.Oak 15" dia., bears S.60°E., 34 lks. dist.

BLM resurvey by James E. Jelley, Cadastral Surveyor - under Group #863, surveyed May/July 1975 - (DCSO records Vol. 38 Page(s) 15571)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

¼ S 14 / S 23
T 28 S R 8 W
1975

from which
A Fir 9" dia., bears N.54 3/4°E., 30 lks. dist. mkd. ¼ S14 BT.
A Fir 10" dia., bears S.60¼°E., 18 lks. dist. mkd. ¼ S23 BT.

Fd. and used in BLM resurvey by James E. Jelley and Wayne L. Rogers, Cadastral Surveyors, under Group #1028, surveyed Oct. 1980/May 1984 - (DCSO records Vol. 45 Page(s) 17392)

Mark Smalley - For: Roseburg Resources - 7/2001 - M 138-50

Found - 1975 BLM brass cap on iron pipe.
12" (9") Fir N.54¾°E., 19.8' healed.
17" (10") Fir S.60¼°E., 11.9' healed.
Scribed- 14" Fir S.44°W., 18.5' "¼ S BT"
8" Fir S.69°W., 33.1' "¼ S BT"

Fd. BC & accessories by R. Quimby, 4/2013 - M157-71
Found as per record - 3/2025 - N. Hibbs - M185-31.