

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 11 and 14

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 14 Page(s) 5805)

-----  
Set ¼ sec. post, from which  
A Fir 8" dia., bears N.56°W., 15 lks. dist.  
A Fir 12" dia., bears S.84°W., 18 lks. dist.

H.L. Eppstein, Co. Surveyor - Wit: Harley Johnson; B.A. Lane; G.C. Sellers - March 4, 1930 - Vol. 4 Pg 9; C.S. File 14/58

-----  
Set a Dodge axle half way on line between section corners. Quarter corner lost, trees gone.  
Marked new BTs:  
Fir 30" dia., bears S.63°E., 82.0 ft.  
Fir 12" dia., bears N.12°W., 120.0 ft.

Floyd Frear - Deputy Surveyor - Wit: D. Owens; Ray Johnson; C. Stubbs; Wm. Cooper - (Date ?) - C.S. file 41/270

-----  
Found 1¼' round axle set by Eppstein. I mark:  
10" Madrone S 11 BT, N.53°E., 23.6 ft.  
14" R.Fir S 14 BT, S.15°E., 49.6 ft.

Douglas Co. Surveyors Office - John M. Powell, and crew - March 3, 1970 - C.S. File 52/79-39

-----  
Found - Axle found at ¼ corner by Eppstein.  
10" now 12" Laurel, N.53°E., 23.6 ft., shows good scar.  
14" now 24" D.Fir S.15°E., 49.6 ft., shows good scar.

Set Brass cap at cor. mkd: County Surveyors Office  
(Set alongside axle) T 28 S R 8 W  
S 11  
S 14  
1970

Bearing trees OK and tagged.  
Corner lies 10 ft. South of E-W fence line approx. 60 ft. West of county road.

Douglas Co. Surveyors Office - Randall Smith and Stephen Flause, crew - Aug. 29, 1984 - C.S. File 62/21-36

-----  
Found - 1970 DCSO brass cap properly mkd., on a I.P. protruding 8" above ground.  
(Cont. Next Page)

TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 540500

PRIMARY CORNER DESCRIPTION 1/4 cor. for Secs. 11 and 14

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

A 1¼" dia. axle shaft that is 1" square on top, protrudes 2" above ground. Axle shaft touches South side of I.P.  
10" now a 17" dia. forked Madrone with a well healed single blaze on South fork, bears N.53°E., 24.5 ft. (Rec. 23.6 ft. is to center of South fork)  
14" now 28" D.Fir with a well healed single blaze bears S.15°E., 50.3 ft. (Rec. 49.6 ft. is to face.)  
New BT - 12" Madrone double blazed and scribed "¼ S11 CS BT" bears N.28°W., 41.7 ft.

Corner Fd. and Used in BLM Resurvey by Dale T. Bedell, Cadastral Surveyor, under Group #1278, Surveyed July/Oct. 1985 - (DCSO records Vol. 48 Page(s) 18254)

Fd. OK, Dec. 1994 by R.L. Dolan - M 121-53  
Fd. BC & accessories by R. Quimby, 4/2013 - M157-71