

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 11

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

BLM Resurvey by Dale T. Bedell, Cadastral Surveyor, under Group #1278, Surveyed July/Oct. 1985 - (DCSO records Vol. 48 Page(s) 18255-56)

-----  
Point for the center ¼ sec. cor. of sec. 11, at intersection with the E. and W. center line.

Set a stainless steel post 28" long, 2½" dia., 24" in the ground with brass cap mkd. T 28 S R 8 W

C ¼  
S 11  
1985

from which

A Hemlock 12" dia., bears S.87°E., 32 lks. dist. mkd. X BT.

A Hemlock 6" dia., bears s.29°W., 16 lks. dist. mkd. C¼ S11 BT.

Deposit white "DEEP-1" magnetic marker at base of stainless steel post.

From this point, the corner of wire fences, extending S. and E., bears N.30°W., 0.48 chs. dist.

From this same point, a monument of which I find no description, bears N.19°02'W., 0.70 chs. dist., a steel axle 1¼" dia., with a wheel hub 6" dia., attached to the top, projecting 2" above ground, from which bearing trees not of record:

A Fir stump 33" dia., bears S.3°E., 25 lks. dist., with healed blaze.

A Fir 35" dia., bears N.30°W., 23½ lks. dist., with healed blaze.

An examination of Douglas Co. Survey File, Vol. 14, Entry 58 (C.S. 14/58), indicates that this monument is at the position of E. and W. center line random point No. 6, established by Eppstein in 1930, during the subdivision of sec. 11, shown on page 9A of Vol. 4 of the survey file, and not at the center of the section.

See C.S. File 62/29-8 for correspondence between the Co. Surveyor's office and the BLM