

TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 571700

PRIMARY CORNER DESCRIPTION So. C C for Secs. 35 & 36, T27-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by William P. Heyden, Deputy Surveyor, under contract #656, dated May 21, 1896 - (DCSO records Vol. 13 Page(s) 5278 and Page 5286)

-----  
(Page 5278)

Set a W.Oak post 3 ft. long, 4" sq., 24" in the ground, for the standard cor. of secs. 35 and 36, marked S C T27S R8W on N.; S36 on E.; and S35 on W. faces, with one groove on E. and 5 grooves on W. faces, from which

A Laurel 16" dia., bears N.20°W., 16 lks. dist. mkd. T27S R8W S35 BT.

A Laurel 8" dia., bears N.10°E., 27 lks. dist. mkd. T27S R8W S36 BT.

(Page 5286)

Find the standard cor. to secs. 35 and 36, a post marked and witnessed as reported by the Examiner, namely: S C T27S R8W on N.; S C T27S R8W S36 on E.; T27S on S.; S C T27S R8W S35 on W. faces, with 1 groove on E. and 5 grooves on W. faces, from which

A Laurel 16" dia. bears N.80°E. 16 lks. mkd. T27S R8W S36 BT

A Laurel 8" dia. bears N.60°W. 25 lks. mkd. T27S R8WS35 BT  
I erase redundant markings on the post, and also the S C on the witness trees.

Survey by Gene E. Johnson - March 15, 1955 - C.S. 42/194-1

-----  
Location of corner determined from testimony of Arthur M. Mathews. (Testimony in C.S. File)

At Corner point, Set 3/4" Iron rod with stake alongside, from which no bearing trees available. Drove climbers rock nail in cliff face, S.46°00'E., 16.0 ft. dist. Rock nail has circular head with 1" dia. steel ring attached.

Survey by Henry Reppeto - For: Weyerhaeuser Co. - Nov. 26, 1979 - C.S. File 58/219 - see also C.S. File 58/271-15

-----  
Found markings on rock wall at the base of 100 ft. high bluff, including "B0 T27S R8W" and "S46E 16", which is the bearing and distance listed by Johnson in 1955. No evidence of piton with circular ring but evidence where originally driven in crack in rock face. Found no trace of 3/4" Iron rod for corner.

Set 1½" Iron pipe with brass cap using Johnson's bearing and distance measured from rock wall described above, from which 6" D.Fir scribed "BT", bears N.52½°E., 16.0 ft.

continued next page

TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 571700

PRIMARY CORNER DESCRIPTION So. C C for Secs. 35 & 36, T27-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Tony Hostetter - For: Seneca Jones Timber Co. - Aug. 2002 - M140-72

-----  
Found - 1979 brass cap & accessories as described by Reppeto  
from which:

New BTs- 14" Fir mkd w/"X", BT tag, bears S.75°E., 16.8 ft.  
to center.

14" Fir mkd w/"X", BT tag, bears S.10°W., 42.5 ft.  
to center.

AMENDED SECTION CORNER ON TOWNSHIP LINE (NOT MONUMENTED)  
BEARS: S.01°12'53"E., 4.58 FT.