

TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 600100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 35 & 36; 1 & 2, T29-8

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 14 Page(s) 5793)

-----  
Set post cor. secs. 35, 36, 1 and 2, from which  
A W.Oak 20" dia., bears S.1°E., 230 lks. dist.  
A W.Oak 24" dia., bears N.75°E., 548 lks. dist.  
A B.Oak 20" dia., bears S.8½°W., 284 lks. dist.  
A B.Oak 24" dia., bears N.82°W., 524 lks. dist.

GL0 resurvey by Fred Mensch, U.S. Cadastral Engineer - under special Instructions, dated May 6, 1924 - (DCSO records Vol. 14 Page(s) 6003-04)

-----  
Intersect the point for cor. of secs. 1, 2, 35 and 36, located by record measurement from the original bearing trees.

At the exact corner point  
Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap mkd:  
T28S : R8W  
S35 : S36  
-----  
S2 S1  
T29S  
1924

from which the original bearing trees:  
A W.Oak, dead, 36" dia., bears N.82½°E., 548 lks. dist. (Not N.75°E.)  
A W.Oak 30" dia., bears S.1°E., 230 lks. dist.  
A B.Oak 30" dia., bears S.8°W., 284 lks. dist.  
A B.Oak 30" dia., bears N.74°W., 524 lks. dist. (Not N.82°W.)

The blazes are plain on all these old trees, marks are grown over and not opened.

New Bearing trees:  
A B.Oak 12" dia., bears N.66°E., 194 lks. dist. mkd. T28S R8W S36 BT.  
A W.Oak 8" dia., bears S.20°E., 139 lks. dist. mkd. T29S R8W S1 BT.  
A W.Oak 14" dia., bears S.8½°W., 218 lks. dist. mkd. T29S R8W S2 BT.  
A W.Oak 16" dia., bears N.59 3/4°W., 478 lks. dist. mkd. T28S R8W S35 BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - Nov. 1966 - C.S. File 54/38-6

-----  
Found - GL0 brass cap at cor., properly mkd. in 1924.  
(Cont. Next Page)

TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 600100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 35 & 36; 1 & 2, T29-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

12" now 14" B.Oak N.66°E., 128.0 ft., rotten face, reverse scribing.  
8" now 11" W.Oak S.20°E., 91.7 ft., shows scar.  
No trace of NW. nor SW. BTs.  
New BTs- 9" double W.Oak S.15°W., 86.0 ft. mkd. T29S R8W S2 CS BT.  
9" D.Fir N.14°E., 29.4 ft. mkd. T28S R8W S36 CS BT  
No trees available in NW. quad.  
This corner lies 1.5 ft. SW. of fence corner.

BLM resurvey by Wayne L. Rogers, Cadastral Surveyor, Group #1483, surveyed May/July 1989 - (DCSO records Vol. 50 Page(s) 18842-43)

-----

The Sec. cor., monumented with an iron post, 1¼" dia., firmly set, projecting 5" above ground, with brass cap mkd. in 1924 from which the remains of bearing trees mkd. by Mensch:  
A sawed Oak stump 18" dia., bears N.66°E., 194 lks. dist., with fragmentary scribe marks visible on opened blaze.  
A W.Oak 15" dia., bears S.20°E., 139 lks. dist., with healed blaze.  
and bearing trees mkd. by Powell in 1966:  
A Fir 15" dia., bears N.15½°E., 45 lks. dist. with healed blaze.  
A double W.Oak 9" dia., bears S.16°W., 128 lks. dist., with healed blaze.  
and a bearing tree of which I have no record:  
A W.Oak 16" dia., bears S.6½°W., 397 lks. dist., with healed blaze.  
and a new bearing tree:  
A W.Oak 5" dia., bears N.19°W., 32 lks. dist. mkd. X BT.

David Edwards - For: Roseburg Resources Co. - 11/2021 - M180-15

-----

Found - Brass cap  
A 20" diam. fir snag bears N.15½°E., 29.7'  
An 18" diam. W.Oak bears S.20°E., 91.7'  
A 12" diam. W.Oak bears S.16°W., 84.5'  
An 8" diam. W.Oak bears N.19°W., 21.1'  
All with healed blazes.