

TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25, 26, 35 and 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 14 Page(s) 5796)

Marked a B.Oak 30" dia. for cor. secs. 25, 26, 35 and 36, from which

- A B.Oak 12" dia., bears S.33°W., 84 lks. dist.
- A B.Oak 10" dia., bears N.87°E., 53 lks. dist.
- A W.Oak 12" dia., bears N.25°W., 80 lks. dist.
- A W.Oak 12" dia., bears S.40°E., 69 lks. dist.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; S. Bilow, crew - Oct. 18, 1957 - C.S. File 49/12-17

Found - US GL0 brass cap at corner.

I can find no trace of any of the original BTs.

BTs scribed in 1924:

- 14" Cedar bears S.31°E., 10.6 ft., shows blaze. I do not open.
 - 14" R.Fir stump, bears N.77½°E., 19.0 ft. I open and find good scribing "W S25 BT".
 - 18" R.Fir bears S.82°W., 31.3 ft., shows blaze. I do not open.
- The NW. BT is down.

- New BTs-
- 12" R.Fir bears N.12°W., 20.3 ft. scribed S26 T28S R8W CS BT.
 - 12" R.Fir bears S.87°E., 60.6 ft. scribed S36 T28S R8W CS BT.
 - 18" R.Fir bears S.82°W., 31.3 ft. rescribed S35 T28S R8W CS BT.

No trees near in NE. quad.

Fd. OK, Feb. 1986 by L. Dolan - M 100-24

BLM resurvey by Wayne L. Rogers, Cadastral Surveyor, Group #1483, surveyed May/July 1989 - (DCSO records Vol. 50 Page(s) 18847-48)

The Sec. Cor., believed to have been remonumented by Mensch in 1924 and perpetuated and recorded by Byron in 1957; although no original evidence remains, it has long been accepted as the corner by the County Surveyors Office and the local landowners; monumented with an iron post 2" dia., firmly set, projecting 10" above ground with brass cap mkd. (Cont. Next Page)

TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25, 26, 35 and 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

T 28 S R 8 W
S 26 | S 25
S 35 | S 36
1924

from which bearing trees believed to have been mkd. by Mensch
A Cedar 26" dia., bears S.29½°E., 16½ lks. dist., with
healed blaze.

A Fir 25" dia., bears S.82°W., 48 lks. dist. with healed
blaze, rescribed by Byron, also healed blaze.

and the remains of bearing trees mkd. by Byron

A Fir snag 13" dia., bears S.87 3/4°E., 90 lks. dist.,
with scribe marks T28S R8W S36 CS visible on open
blaze.

A sawed Fir stump 18" dia., bears N. 16 3/4°W., 33 lks.
dist. with scribe mark T visible on opened blaze.

and new bearing trees

A Fir 7" dia., bears N.40½°E., 55 lks. dist. mkd. T28S R8W
S25 BT.

An Oak 4" dia., bears N.55½°W., 26 lks. dist. mkd. T28S
R8W S26 BT.