

TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 600240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 25 and 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 14 Page(s) 5797)

Marked a Laurel 20" dia., for ¼ sec. cor., from which
An Oak 9" dia., bears S.55°W., 22 lks. dist.
A Laurel 10" dia., bears S.48°E., 47 lks. dist.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; S. Bilow, crew - Oct. 16, 1957 - C.S. File 49/12-16

Found - Brass cap at corner mkd. US GL0 1924 ¼ S26|S25.
Neither original bearing tree can be found at this time, but I find clump of laurel at record distance and bearing for SW. BT.
21" R.Fir bears N.82°E., 56.2 ft. shows good face.
I do not open. (1924 BT)
10" R.Fir bears N.68°W., 26.5 ft. I open, find scribe marks "¼ S 26" (1924 BT)
New BTs- 21" R.Fir bears N.82°E., 56.2 ft. bark scribed ¼ S25 CS BT.
15" R.Fir bears N.80°W., 55.7 ft. scribed ¼ S26 CS BT.

Note: (No recorded 1924 GL0 survey found)

Cor. found and used in BLM resurvey by Wayne L. Rogers, Cadastral Surveyor, Group #1483, surveyed May/July 1989 - (DCSO records Vol. 50 Page(s) 18849)

Carl Sweeden - For: Emma Wageman Trust - June 2012 - M163-67

Found - 2½" GL0 BRASS CAP "1924" up 1.60'
21" R.Fir, N.82°E., 55.4' (56.2), tag & scar vis.
10" R.Fir, N.68°W., 26.5' to root hole
34" R.Fir, N.80°W., 54.8' (55.7'), tag & scar vis.
New - 20 Fir, N.22°W., 69.1', tag & scribed "S26 E¼ BT"
32" Fir, S.1°E., 34.2', tag & scribed "S25 W¼ BT"