

TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 600300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 23, 24, 25 and 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 14 Page(s) 5797)

Set post cor. secs. 23, 24, 25 and 26, from which
An Oak 15" dia., bears S.89°E., 91 lks. dist.
An Oak 20" dia., bears N.15°E., 75 lks. dist.
An Oak 18" dia., bears N.74°W., 42 lks. dist.
An Oak 12" dia., bears S.68°W., 94 lks. dist.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; S. Bilow, crew - Oct. 16, 1957 - C.S. File 49/12-15

Found - Brass cap at corner marked US GL0 Survey 1924 S23 S24 S26 S25 T28S R8W.
Orig. BT, 18" now 30" B.Oak N.74°W., 27.7 ft. On chip from old face, find scribing "W S".
All other original BTs gone.
18" dead R.Fir, I open scribed "W S 26 BT", bears S.45°W. (1924 BT)
26" R.Fir shows good blaze, I do not open, bears S.54°E., 14.3 ft. (1924 BT)
20" R.Fir shows good blaze, I do not open, bears N.51°W., 28.5 ft. (1924 BT)
New BTs- 10" W.Fir bears S.38°W., 36.8 ft. scribed S26 T28S R8W CS BT.
14" W.Fir bears S.34½°E., 22.9 ft. scribed S25 T28S R8W CS BT.
8" W.Fir bears N.78°E., 31.2 ft. scribed S24 T28S R8W CS BT.
20" R.Fir bears N.51°W., 28.5 ft. scribed S23 T28S R8W CS BT.

BLM resurvey by James E. Jelley, Cadastral Surveyor - under Group #863, surveyed May/July 1975 - (DCSO records Vol. 38 Page(s) 15566)

The Sec. Cor. rehabilitated by Fred Mensch, in 1924, and not of record, monumented with an iron post 2" dia., firmly set, projecting 1" above ground with brass cap mkd. in 1924 from which bearing trees mkd. by Mensch in 1924, and not of record:

A Fir 30" dia., bears S.51½°E., 22 lks. dist., with healed blaze.
A root hole bears S.48½°W., 32 lks. dist. with a down Fir alongside, 18" dia., with fragmentary scribe marks visible on open blaze.

(Cont. Next Page)

TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 600300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 23, 24, 25 and 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Fir 25" dia., bears N.49½°W., 43 lks., with healed blaze and bearing trees mkd. by Byron in 1957
A Fir 18" dia., bears N.80¾°E., 47½ lks. with healed blaze
A Fir 20" dia., bears S.31¾°E., 34½ lks. with healed blaze
A Fir 15" dia., bears S.39°W., 56 lks., with healed blaze
A Fir 22" dia., bears N.49¾°W., 43 lks., with healed blaze
ADD MARKS 1975 TO BRASS CAP.

Dan Saily, Lone Rock Timber - Crew: Brett Ragon, Ignacio Roman, Trevor Clemo & Weston Addington - 4/2023 - M182-25

Found - 1924 GLO brass cap (properly) mkd. The top of the monument is flush with ground and we set a galvanized steel post 1 foot north.
34" D.Fir bears S.45¾°E., 13.9 ft (record S.51½°E., 22 lks) with well healed face and tag
34" W.Fir bears S.35°E., 22.5 ft (record S.31¾°(E) 34½ lks) with well healed face and BLM tag
34" W.Fir bears S.37°W., 36.8 ft (record S.39°W., 56 lks) with well healed face and BLM tag
19"x 6' tall D.Fir rotten stump bears N.52°W., 28.3 ft (record N.49¾°W., 43 lks). Visible scribe reads T28S R8W S23 CS with no tag
New - 12" D.Fir bears N.33¾°W., 11.6 ft scribed S23 BT and tagged
14" W.Fir bears N.70½°E., 13.0 ft scribed S24 BT and tagged.

Fd ok - Dan Saily For: Lone Rock - 7/2025 - CS 65/115-002