

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 13 and 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 14 Page(s) 5799)

-----

Marked an Ash 6" dia. for 1/4 sec. cor., from which  
 An Ash 9" dia., bears N.50°E., 3 lks. dist.  
 An Ash 10" dia., bears S.60°W., 4 lks. dist.

Survey by Roger H. Gee - For: Liles - Filed May 1971 - M 41-67

-----

Set 1" I.Pipe for WITNESS CORNER by proportionate measurement (1/4 cor. bears N.1°12'45"E., 11.26 ft.) From Witness Corner:  
 8" Ash bears N.62°51'W., 12.4 ft. mkd. "WC 1/4 S14 BT"  
 8" Ash bears S.54°37'E., 13.0 ft. mkd. "WC 1/4 S13 BT"

David Edwards - For: Seneca Jones Tbr Co - 8/2009 - M159-62

-----

The iron pipe witness corner for the west 1/4 corner, per M41-67, was found out of the ground lying next to what appeared to be Gee's southerly BT. The other BT is gone & his 1/4 corner position could not be determined. I compute my own proportionate position.  
 NOT FOUND.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 9/2/2009 - C.S. File 67/28-36

-----

Found - 1971 1" I.D. x 32" long iron pipe out of ground.  
 8" now 9" dia., Ash with partially healed double blaze scribing visible "WC 1/4 S13 BT"

Set - 1971 iron pipe at 1/4 corner position determined from SE WC BT N.54 1/2°W., 13.0 ft., thence N.1 1/4°E., 11.3 ft. IP protrudes 6" out of creek bottom.  
 From 1971 I.P. in creek bottom, a 2 1/2" dia., brass cap on a 1 1/2" dia., by 32" long iron pipe is set as an R.M. corner West 50.0 ft. DCSO RM BC IP protrudes 6" out of ground. Brass cap mkd:

DOUGLAS COUNTY SURVEYORS  
 T28S  
 1/4 RM R  
 S 14 | S 13 8  
 COR EAST W  
 50 FT  
 2009

1971 SW WC BT bears S.29°E., 21.5 ft. from set IP at 1/4 corner in crk bottom.

continued next page

TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 600440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 13 and 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

From 2009 DCSO RM/IP  
12" dia. D.Fir double blazed & scribed "RM ¼ S14 CS  
BT" bears N.69¼°E., 15.1 ft.  
6" dia., D.Fir double blazed & scribed "RM S14 ¼ CS  
BT" bears S.77°W., 6.3 ft.  
Note - 1971 ¼ corner and WC corner positions now both fall  
in creek bottom.  
We perpetuate position of 1971 corner per M41-67.  
Compass decl. 17¼°E.

Fd. BC & accessories by R. Quimby, 4/2013 - M157-71