

TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 600500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 11, 12, 13 and 14

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 14 Page(s) 5799)

-----  
Set post cor. secs. 11, 12, 13 and 14, from which  
A B.Oak 16" dia., bears N.52°E., 37 lks. dist.  
A B.Oak 14" dia., bears N.81°W., 56 lks. dist.  
A W.oak 12" dia., bears S.52°E., 44 lks. dist.  
A Fir 24" dia., bears S.80°W., 69 lks. dist.

H.L.Eppstein, Co. Surveyor - Wit: Harley Johnson; B.A. Lane; G.C. Seller - March 4, 1930 - C.S. File 14/58; Vol. 4 Pg. 9

-----  
Set post for corner from old BTs, namely,  
A Fir SW. and an Oak NE.  
Marked:  
Fir 5" dia., bears N.39°W., 52.0 ft. for witness tree.  
No other tree in the other sections near.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; J. Fee, crew - Aug. 1957 - C.S. File 49/12-4

-----  
Found - 1 3/4" steel axle at corner.  
D.Fir now 7" dia., N.39°W., 51.2 ft., chopped out lower blaze and found scribe "BT", very plain.  
Rotted remnants of Oak stump N.52°E., 25.5 ft. to center. No scribing found. Stump was too far gone.  
No evidence found of other original BTs.  
New BTs- 7" Madrone S.49°W., 22.2 ft. scribe T28S R8W S14 CS BT.  
6" Madrone N.73°E., 11.1 ft. scribe T28S R8W S12 CS BT.  
7" Madrone S.70°E., 7.5 ft. scribe T28S R8W S13 CS BT.

BLM Resurvey by Dale T. Bedell, Cadastral Surveyor, under Group #1278, Surveyed July/Oct. 1985 - (DCSO records Vol. 48 Page(s) 18254-55)

-----  
The Sec. cor., perpetuated and recorded by Eppstein in 1930, monumented with a steel rod, 1½" dia., firmly set, projecting 3" above ground, from which the remains of an original bearing tree:  
A rotted Oak root crown, bears N.52°E., 37 lks. dist., no marks remaining.  
and a bearing tree mkd. by Eppstein:  
(Cont. Next Page)

TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 600500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 11, 12, 13 and 14

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

A Fir 15" dia., bears N.39°W., 80 lks. dist., with healed double blaze.

and bearing trees mkd. by Byron in 1957:

A Madrone 8" dia., bears N.74°E., 16½ lks. dist., with healed blaze.

A Madrone 10" dia., bears S.70°E., 11½ lks. dist., with healed double blaze.

A Madrone 11" dia., bears S.49°W., 34 lks. dist., with healed double blaze.

At the corner point

Set an stainless steel post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd:

T 28 S R 8 W  
S 11 | S 12  
S 14 | S 13  
1985

Deposit the steel rod alongside the corner.

Corner is on a SE. slope, at a fence corner, wire fences extending N. and S.70°W.

Fd. OK, Dec. 1994 by R. Dolan - M 121-53

FD. Ok by D. Edwards, 8/2009 - M159-62

Fd. by D. Edwards, as per M110-38 3/2016